, This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

NORDIA

SVR SILICONE

.1	Product identifier:	SVR SILICONE				
	Other means of identification:					
	Non-applicable					
1.2	Relevant identified uses of the substance or mixture and uses advised against:					
	Relevant uses: Decorative Emul	ion Plaster				
	Uses advised against: All uses no	t specified in this section or in section 7.3				
1.3	Details of the supplier of the sa	ety data sheet:				
	NORDIA S.A. 364 Kifisias Av. 15233 Chalandri - Greece Phone: +30 22950 22225 - Fax: - info@marmoline.gr www.marmoline.gr	30 22950 22120				
1.4	Emergency telephone number:	+30 210 7793 777 (Greek Poison Info Center)				
SECT 2.1	ION 2: HAZARDS IDENTIFICA Classification of the substance					
	Caution: Due to the existence of not individually provided for the	neutralisation ($5 < pH < 9$) between the product's components, the hazards in terms of corrosion potent substances.	ial are			
		08:				
	CLP Regulation (EC) No 1272/20					
	• • • •	been carried out in accordance with CLP Regulation (EC) No 1272/2008.				
	Classification of this product ha	been carried out in accordance with CLP Regulation (EC) No 1272/2008. the aquatic environment, long-term hazard, Category 3, H412				

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P273: Avoid release to the environment.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aqueous mixture composed of additives, aggregates, pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

** Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

NORDIA

SVR SILICONE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

	Identification		Chemical name/Classification		Concentration	
CAS: 1336-21-6		Ammonia = 25 %, aqueous solution ⁽¹⁾ ATP CLP00				
EC: Index: REACH:	215-647-6 007-001-01-2 01-2119982985-14-XXXX	Regulation 1272/2008 Aqua	atic Acute 1: H400; Skin Corr. 1B: H314; STOT SE 3: H335 - Danger		<5 %	
CAS:	2634-33-5	1,2-benzisothiazol-3(2H)-one ⁽¹⁾		Self-classified		
EC: Index: REACH:	220-120-9 613-088-00-6 01-2120761540-60-XXXX		e Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Irrit. 2: H315; Skin Sens. 1: H317 - Danger		<0,05 %	
CAS:	13463-41-7	Pyrithione zinc ⁽¹⁾		ATP ATP15	inhalation: ATE < 0.14 mg/L	
EC: Index: REACH:	236-671-3 613-333-00-7 01-2119511196-46-XXXX		e Tox. 2: H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1:); Eye Dam. 1: H318; Repr. 1B: H360D; STOT RE 1: H372 - Danger) () () () () () () () () () () () () ()	(dusts/mists) oral: ATE < 221 mg/kg bw (-)	
CAS:	886-50-0	Terbutryn ⁽¹⁾ Self-classified				
EC: Index: REACH:	212-950-5 Non-applicable Non-applicable	Regulation 1272/2008 Acute Warn	e Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1B: H317 - ning	۲	<3 %	
CAS:	55965-84-9	reaction mass of 5-chloro-2-met	thyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) ⁽¹⁾	ATP ATP13		
EC: Index: REACH:	Non-applicable 613-167-00-5 Non-applicable		e Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1:); Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger		<0,0015 %	
CAS:	50-00-0	Formaldehyde ⁽²⁾		ATP ATP06		
EC: Index: REACH:	200-001-8 605-001-00-5 01-2119488953-20-XXXX	J .	e Tox. 3: H301+H311+H331; Carc. 1B: H350; Muta. 2: H341; Skin Corr. 1B: H314; Skin . 1: H317 - Danger	***	<0,2 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 (2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

	Identification			M-factor
Pyrithione zinc			Acute	1000
CAS: 13463-41-7	EC: 236-671-3		Chronic	10
Terbutryn			Acute	100
CAS: 886-50-0	EC: 212-950-5	Chronic	100	
reaction mass of 5-chl	oro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	3:1)	Acute	100
CAS: 55965-84-9	EC: Non-applicable		Chronic	100
	Identification	Spe	cific concentr	ation limit
1,2-benzisothiazol-3(2 CAS: 2634-33-5 EC: 220-120-9	H)-one	% (w/w) >=0,05: Skin Sens. 1 - H317		
Terbutryn CAS: 886-50-0 EC: 212-950-5		% (w/w) >=3: Skin Sens. 1 - H317		
reaction mass of 5-chl (3:1) CAS: 55965-84-9 EC: Non-applicable	oro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	 % (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317 		
Formaldehyde CAS: 50-00-0 EC: 200-001-8		% (w/w) >=25: Skin Corr. 1B - H: 5<= % (w/w) <25: Skin Irrit. 2 - H % (w/w) >=25: Eye Dam. 1 - H33 5<= % (w/w) <25: Eye Irrit. 2 - H % (w/w) >=0,2: Skin Sens. 1 - H3 % (w/w) >=5: STOT SE 3 - H335	1315 18 319	

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

SVR SILICONE

SECTION 4: FIRST AID MEASURES (continued)

By skin contact:

NORDIA

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. **Unsuitable extinguishing media:**

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

SVR SILICONE

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

NORDIA

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

- A.- Technical measures for storage
 - Minimum Temp.:5 °CMaximum Temp.:30 °CMaximum time:12 Months
- B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation): Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
Formaldehyde	IOELV (8h)	0,3 ppm	0,37 mg/m ³	
CAS: 50-00-0 EC: 200-001-8	IOELV (STEL)	0,6 ppm	0,74 mg/m ³	

DNEL (Workers):

		Short	t exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,966 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6,81 mg/m ³	Non-applicable
Pyrithione zinc	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 13463-41-7	Dermal	Non-applicable	Non-applicable	0,01 mg/kg	Non-applicable
EC: 236-671-3	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Formaldehyde	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	240 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	0,75 mg/m ³	9 mg/m ³	0,375 mg/m ³

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



SVR SILICONE

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

				-	
		Short e	xposure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1,2 mg/m ³	Non-applicable
Formaldehyde	Oral	Non-applicable	Non-applicable	4,1 mg/kg	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	102 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	Non-applicable	3,2 mg/m ³	0,1 mg/m³

PNEC:

Identification				
1,2-benzisothiazol-3(2H)-one	STP	1,03 mg/L	Fresh water	0,00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0,000403 mg/L
EC: 220-120-9	Intermittent	0,0011 mg/L	Sediment (Fresh water)	0,0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00499 mg/kg
Pyrithione zinc	STP	0,01 mg/L	Fresh water	0,00009 mg/L
CAS: 13463-41-7	Soil	1,02 mg/kg	Marine water	0,00009 mg/L
EC: 236-671-3	Intermittent	Non-applicable	Sediment (Fresh water)	0,009 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg
Formaldehyde	STP	0,19 mg/L	Fresh water	0,44 mg/L
CAS: 50-00-0	Soil	0,2 mg/kg	Marine water	0,44 mg/L
EC: 200-001-8	Intermittent	4,44 mg/L	Sediment (Fresh water)	2,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	2,3 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Viton®-Butyl, Breakthrough time: > 480 min, Thickness: 0.7 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

NORDIA

SVR SILICONE

	Pictogram		PPE	Labelling	CEN Standard		Remarks
		Anti-	slip work shoes	CAT II	EN ISO 20347:2012	pro	ce before any evidence of deterioration. For p of prolonged exposure to the product for 'essional/industrial users CE III is recommende rdance with the regulations in EN ISO 20345:20 EN 13832-1:2007
F Ac	ditional emergend	cy measur	res				
	Emergency meas	sure	S	tandards	Emergency n	neasure	Standards
	^ +			NSI Z358-1 D11, ISO 3864-4:2011			DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Enviro	Emergency show		5:		Eyewash st	ations	
In acco	onmental exposure	e controls communit	y legislation for th	•	e environment it is reco		to avoid environmental spillage of b
In acco the pro	onmental exposure	e controls communit ainer. For	y legislation for th	•	e environment it is reco		l to avoid environmental spillage of bo
In acco the pro Volati	onmental exposure ordance with the c oduct and its conta	e controls communit ainer. For unds:	y legislation for th additional inform	ation see subsect	e environment it is reco ion 7.1.D		I to avoid environmental spillage of be
In acco the pro Volati With r	onmental exposure ordance with the c oduct and its conta le organic compo	e controls communit ainer. For unds:	y legislation for th additional inform /EU, this product h	ation see subsect	e environment it is reco ion 7.1.D		to avoid environmental spillage of bo
In acco the pro Volati With r V.	onmental exposure ordance with the c oduct and its conta le organic compou egard to Directive	e controls communit ainer. For unds: 2010/75/	y legislation for th additional inform /EU, this product h 0,3 %	ation see subsect	e environment it is reco ion 7.1.D		I to avoid environmental spillage of be
In acco the pro Volati With r V. V.	onmental exposure ordance with the c oduct and its conta le organic compou egard to Directive O.C. (Supply):	e controls communit ainer. For unds: 2010/75/ ºC:	y legislation for th additional inform /EU, this product h 0,3 %	ation see subsect has the following of weight	e environment it is reco ion 7.1.D		to avoid environmental spillage of bo
In acco the pro Volati With r V. V.	onmental exposure ordance with the c oduct and its conta le organic compou- egard to Directive O.C. (Supply): O.C. density at 20	e controls communit ainer. For unds: 2010/75/ ºC: nber:	y legislation for th additional inform /EU, this product h 0,3 % 5,7 kg 9	ation see subsect has the following of weight	e environment it is reco ion 7.1.D		I to avoid environmental spillage of be
In acco the pro Volati With r V. V. Av	onmental exposure ordance with the c oduct and its conta le organic compou egard to Directive O.C. (Supply): O.C. density at 20 verage carbon num verage molecular v	e controls communit ainer. For unds: 2010/75/ ºC: nber: veight:	y legislation for th additional inform /EU, this product H 0,3 % 5,7 kg 9 119,9	ation see subsect has the following of weight :/m³ (5,7 g/L) 5 g/mol	e environment it is reco ion 7.1.D	ommended	
In acco the pro Volati With r V. V. Av Av With r	onmental exposure ordance with the c oduct and its conta le organic compou egard to Directive O.C. (Supply): O.C. density at 20 verage carbon num verage molecular v	e controls communit ainer. For unds: 2010/75/ ºC: nber: veight: 2004/42/	y legislation for th additional inform /EU, this product h 0,3 % 5,7 kg 9 119,9 /EC, this product v	ation see subsect has the following of weight :/m³ (5,7 g/L) 5 g/mol	e environment it is reco ion 7.1.D characteristics:	ommended	
In acco the pro Volati With r V. V. Av Av With r	onmental exposure ordance with the c oduct and its conta le organic compou- egard to Directive O.C. (Supply): O.C. density at 20 verage carbon num verage molecular v egard to Directive	e controls communit ainer. For unds: 2010/75/ ºC: veight: 2004/42/ ºC:	y legislation for th additional inform /EU, this product H 0,3 % 5,7 kg 9 119,9 /EC, this product v 17,1 k	ation see subsect has the following of weight /m ³ (5,7 g/L) 5 g/mol vhich is ready to u g/m ³ (17,1 g/L)	e environment it is reco ion 7.1.D characteristics:	ommended	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical properties:					
	For complete information see the product datasheet.					
	Appearance:					
	Physical state at 20 °C:	Liquid				
	Appearance:	Paste				
	Colour:	White				
	Odour:	Soft				
	Odour threshold:	Non-applicable *				
	Volatility:					
	Boiling point at atmospheric pressure:	104 ºC				
	Vapour pressure at 20 ºC:	2322 Pa				
	Vapour pressure at 50 °C:	12227,75 Pa (12,23 kPa)				
	Evaporation rate at 20 ºC:	Non-applicable *				
	Product description:					
	Density at 20 ºC:	1900 kg/m³				
	Relative density at 20 ºC:	Non-applicable *				
	Dynamic viscosity at 20 ºC:	Non-applicable *				
	Kinematic viscosity at 20 ºC:	Non-applicable *				
	Kinematic viscosity at 40 ºC:	>20,5 mm²/s				
	Concentration:	Non-applicable *				
	*Not relevant due to the nature of the product, not providing information ${\sf p}$	roperty of its hazards.				

, This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



SVR SILICONE

SECT	ION 9: PHYSICAL AND CHEMICAL PROPERTIES (conti	inued)
	pH:	8,5 - 9,5
	Vapour density at 20 ºC:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 ºC:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	Non Flammable (>60 ºC)
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	275 ºC
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard classes:	
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 ºC:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing informatio	in property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2) , carbon monoxide and other organic compounds.

** Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

NORDIA

SVR SILICONE

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - IARC: Formaldehyde (1); Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (3); Talc (3); Distillates (petroleum), hydrotreated heavy naphthenic (3)
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:
 - Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acut	e toxicity	Genus
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	Non-applicable	
EC: 220-120-9	LC50 inhalation	Non-applicable	

** Changes with regards to the previous version

, This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



SVR SILICONE

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Identification	Ad	Acute toxicity	
Pyrithione zinc	LD50 oral	221 mg/kg	Rat
CAS: 13463-41-7	LD50 dermal	Non-applicable	
EC: 236-671-3	LC50 inhalation	0,14 mg/L (4 h)	Rat
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87,12 mg/kg	Rabbit
EC: Non-applicable	LC50 inhalation	0,33 mg/L (4 h)	Rat
Formaldehyde	LD50 oral	100 mg/kg	
CAS: 50-00-0	LD50 dermal	300 mg/kg	
EC: 200-001-8	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Ammonia = 25 %, aqueous solution	LC50	0,89 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1336-21-6	EC50	101 mg/L (48 h)	Daphnia magna	Crustacean
EC: 215-647-6	EC50	Non-applicable		
1,2-benzisothiazol-3(2H)-one	LC50	2,2 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 2634-33-5	EC50	3 mg/L (48 h)	Daphnia magna	Crustacean
EC: 220-120-9	EC50	0,067 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Pyrithione zinc	LC50	0,003 mg/L (96 h)	Pimephales promelas	Fish
CAS: 13463-41-7	EC50	0,008 mg/L (48 h)	Daphnia magna	Crustacean
EC: 236-671-3	EC50	Non-applicable		
Terbutryn	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 886-50-0	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 212-950-5	EC50	>0.1 - 1 mg/L (72 h)		Algae
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: Non-applicable	EC50	>0.1 - 1 mg/L (72 h)		Algae
Formaldehyde	LC50	100 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 50-00-0	EC50	42 mg/L (24 h)	Daphnia magna	Crustacean
EC: 200-001-8	EC50	Non-applicable		

Chronic toxicity:

Identification	Concentration		Species	Genus
Pyrithione zinc	NOEC	Non-applicable		
CAS: 13463-41-7 EC: 236-671-3	NOEC	0,022 mg/L	Daphnia magna	Crustacean
Formaldehyde	NOEC	Non-applicable		
CAS: 50-00-0 EC: 200-001-8	NOEC	6,4 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

** Changes with regards to the previous version



SVR SILICONE

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Degradability Biodegradability		ility	
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %
Formaldehyde	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 50-00-0	COD	Non-applicable	Period	14 days
EC: 200-001-8	BOD5/COD	Non-applicable	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccun	nulation potential
Ammonia = 25 %, aqueous solution	BCF	
CAS: 1336-21-6	Pow Log	-0.64
EC: 215-647-6	Potential	
1,2-benzisothiazol-3(2H)-one	BCF	2
CAS: 2634-33-5	Pow Log	1.45
EC: 220-120-9	Potential	Low
Formaldehyde	BCF	3
CAS: 50-00-0	Pow Log	0.35
EC: 200-001-8	Potential	Low

12.4 Mobility in soil:

Identification	Absorpti	on/desorption	Volati	ity
Formaldehyde	Кос	Non-applicable	Henry	Non-applicable
CAS: 50-00-0	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-001-8	Surface tension	1,416E-2 N/m (25 ºC)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

SVR SILICONE

SECTION 14: TRANSPORT INFORMATION

NORDIA

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains reaction mass of 5-chloro-2methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13); Pyrithione zinc (Product-type 2, 6, 7, 9, 10, 21); Terbutryn (Product-type 7, 9, 10); reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13); Formaldehyde (Product-type 2, 3, 22)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, -tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

· New declared substances

- 1,2-benzisothiazol-3(2H)-one (2634-33-5) · Removed substances
- 1,2-benzisothiazol-3(2H)-one (2634-33-5)
- CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): Substances contained in EUH208:

 - New declared substances
 - 1,2-benzisothiazol-3(2H)-one (2634-33-5)
 - · Removed substances
 - 1,2-benzisothiazol-3(2H)-one (2634-33-5)

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

, This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

NORDIA

SVR SILICONE

ION 16: OTH	ER INFORMATION (continued)
Acute Tox. 2	: H310+H330 - Fatal in contact with skin or if inhaled.
Acute Tox. 2	: H330 - Fatal if inhaled.
Acute Tox. 3	: H301 - Toxic if swallowed.
Acute Tox. 3	: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.
Acute Tox. 4	: H302 - Harmful if swallowed.
Aquatic Acu	e 1: H400 - Very toxic to aquatic life.
Aquatic Chro	nic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chro	nic 2: H411 - Toxic to aquatic life with long lasting effects.
Carc. 1B: H3	50 - May cause cancer.
Eye Dam. 1:	H318 - Causes serious eye damage.
Muta. 2: H34	11 - Suspected of causing genetic defects.
Repr. 1B: H3	60D - May damage the unborn child.
Skin Corr. 1E	:: H314 - Causes severe skin burns and eye damage.
	: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2:	H315 - Causes skin irritation.
Skin Sens. 1:	H317 - May cause an allergic skin reaction.
	A: H317 - May cause an allergic skin reaction.
	3: H317 - May cause an allergic skin reaction.
	1372 - Causes damage to organs through prolonged or repeated exposure.
STOT SE 3: H	335 - May cause respiratory irritation.
Classification	n procedure:
Aquatic Chro	nic 3: Calculation method
Advice relat	ed to training:
Training is re	commended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretat
of this safety	data sheet, as well as the label on the product.
Principal bib	liographical sources:
http://echa.	europa.eu
http://eur-le	x.europa.eu
Abbreviatio	ns and acronyms:
ADR: Europe	an agreement concerning the international carriage of dangerous goods by road
	ational maritime dangerous goods code
	tional Air Transport Association
	ational Civil Aviation Organisation
COD: Chemi	al Oxygen Demand
BOD5: 5day	piochemical oxygen demand
BCF: Biocond	entration factor
LD50: Lethal	Dose 50
LC50: Lethal	Concentration 50
EC50: Effecti	ve concentration 50
LogPOW: Oc	tanolwater partition coefficient
	n coefficient of organic carbon
UFI: unique f	ormula identifier
IAPC: Intorn	itional Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.