

Unique identification code of the product: MARMOLINE ST 60 CEM

Type: Polymer modified cementitious putty

It refers to all batches of MARMOLINE ST 60 CEM, produced after the issue of the present declaration

Intended use /es: General purpose plaster for internal or external use (GP/CSII)

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece. Manufacturing plant: 1st klm Country road Markopoulou-Oropou, 19014 Polydendri Attikis/ Greece, tel: +302295022225

Systems of AVCP: 4

Harmonized standards: EN 998-1:2016

Notified body/ies: -

Declared performance /s:

| Essential characteristics | Performance | Harmonised technical spec. |
|--|---|---|
| Capillary water absorption: | W _{c0} | EN 998-1:2016 – Table 2 - L5 EN 1015-18 |
| Water vapour diffusion coef.: | μ=15/35 | EN 998-1:2016 – Table 2 - L8 EN 1745 |
| Adhesion after weathering cycles : | 0.5 N/mm ² (FPb) | EN 998-1:2016 – Table 2 - L3 EN 1015-12 |
| Thermal conductivity: | λ _{10,dry} = 0.53 W/mK (tab. mean value; P= 50%) | EN 998-1:2016 – Table 2 - L9 EN 1745 |
| Durability (against freeze/thaw in the place of use): | NPD | EN 998-1:2016 – 5.2.3.2 |
| Reaction to fire: | Class A1 (without testing – organic content < 1,0% - 96/603/EC) | EN 998-1:2016 – 5.2.3.2 & Table 2 - L3, L5 |
| Dangerous substances: | See product’s SDS | EN 998-1:2016 – 5.3.4 & Table 2 - L13 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Polydendri, 1/6/2023

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211819
364 KIFISSIAS AVENUE
CHALANDRI 15233 - ATHENS GR
TEL: 0030 - 210 - 68 96 480
FAX: 0030 - 210 - 68 53 440

Vivi Dilaveri
Director of Marmoline Business Unit, Nordia S.A