

## METALWOOD

### HIGH QUALITY ALKYD-BASED PAINT

**Description :** High quality enamel paint with anti-corrosive properties.

**Usages:** Suitable for metal and wooden surfaces, such as railings, doors, windows, vehicle bodies, furniture etc.

It has excellent resistance to wash and yellowing, providing a perfect finish.



**Advantages:**

- Strong adhesion and hardness
- Resistant to impact and wear
- Retains its shine and hue

**Packaging /distribution:** Available in 750 ml & 2.5 lt metal cans

**Storage:** Protect from freezing. Store at room temperatures, from 5°C to 35°C.  
Seal the container for future use.

**Health and safety :** Pay attention on the safety instructions marked on the product's packaging. Refer to the product's Safety Data Sheet for further information.

After use, carefully seal the container for future use. Do not dispose the product's residue in the drain or in household garbage. Handle empty packages according to existing legislation.

**VOC (Volatile organic compounds):** Subject to directive 2004/42/E.C.: VOC class: "One- pack performance coatings (SB) (A/i)". Limit value for this product: 500 g/l (2010). This product ready for use contains max V.O.C. 499g/l.

**TECHNICAL CHARACTERISTICS:**

<b>Colours:</b>	Available in white, dark green and black as well as in an unlimited number of color shades, through DÉCOR TINTING SYSTEM
<b>Specific gravity:</b>	1.00 - 1.40 gr/ml (ISO 2811)
<b>Viscosity:</b>	180 – 220 s (Ford Cup No 4)
<b>Drying:</b>	4-8 hours
<b>Gloss degree at 60°:</b>	85 – 90%

**APPLICATION:**

<b>Performance:</b>	13 – 15 m <sup>2</sup> / lt
<b>Application mode:</b>	Roller, brush or spray gun
<b>Dilution:</b>	For application with brush or roller, dilute up to 10% with white spirit or brush thinner. For application with spay gun, dilute up to 15% with nitro or spray gun thinner.
<b>Instructions for use:</b>	<ul style="list-style-type: none"><li>• Prepare the application surface, so that it is clean and dry, free of dust, grease or oils, disintegrated parts etc.</li><li>• Ensure good ventilation of the application area and wear appropriate protective means.</li><li>• For better anti-corrosive protection under hard weather conditions, it is suggested prior priming of the surfaces with MARMOLINE Rust Off</li><li>• For application on wooden surfaces, these should first be prepared with a suitable white undercoat (velatura)</li><li>• MARMOLINE MetalWood should be used in well ventilated area</li><li>• It is not suggested to use the products in temperatures below 5°C and above 40°C</li><li>• Remove from the tools the product that is left over, before cleaning them with solvent.</li></ul>
<b>Recoating:</b>	After 24 hours

*We guarantee the quality of all our products, on the basis of their technical specifications, as described in this technical data sheet. Such guarantee refers only to the product that we deliver for use and not to its application or final result, which largely depends on the experience of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version*