

**Unique identification code of the product: MARMOLINE TOP COAT PRIMER**

Type: Primer for coloured epoxy-based, solvent-free coating system

It refers to all batches of MARMOLINE TOP COAT PRIMER, produced after the issue of the present declaration

**Intended use /es:**

Concrete injection product for force transmitting filling of cracks (method 4.5, 4.6)

**Manufacturer /Distributor:**

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, Factory tel: +302295022225

**Systems of AVCP: 2+**

**Harmonized standards:** EN 1504-5 :2004

**Notified body/ies:** TUV AUSTRIA HELLAS (0906)

**Declared performance /s:** U(F1)W(8)(1/2)(5/38)(0)

Essential characteristics	Performance	Harmonised technical spec.
Adhesion by tensile bond strength	Failure on substrate	EN 12618-2
Adhesion by slant shear strength	Monolithic failure (παρόμοια με τη μορφή αστοχίας του δοκιμίου ελέγχου)	EN 12618-3
Injectability into dry medium Crack width 0,8 mm. Determination of injectability and splitting test	Splitting test > 7N/mm <sup>2</sup> Percentage of the crack filled >90%	EN 1771 EN 12618-2
Injectability into non-dry medium Crack width 0,8 mm. Determination of injectability and splitting test	Splitting test > 7N/mm <sup>2</sup> Percentage of the crack filled >90%	EN 1771 EN 12618-2
Shrinkage	< 3%	EN 12617-2
Viscosity	1.8 mPa s	EN ISO 3219
Workable time	22 min	EN ISO 9514
Tensile strength development for polymers	Tensile strength >3 N/mm <sup>2</sup> within 72h at the minimum use temperature	EN 1543
Compatibility with concrete: Adhesion by tensile bond strength	Cohesive failure in the concrete	EN 12618-2
Corrosion Behavior	Non corrosive	According to §5.3
Release of dangerous substances	pass	According to §5.4
Glass transition temperature	> 40° C	EN 12614

**The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:**

Polydendri, 1/6/2023

NORDIA S.A.  
QUARRYING AND INDUSTRIAL  
AND COMMERCIAL CO.S.A.  
VAT: EL 999211319  
364 KIFISSIAS AVENUE  
CHALANDRI 15233 ATHENS GR  
TEL: 0030 - 210 - 68 96 480  
FAX: 0030 - 210 - 68 53 410

Vivi Dilaveri  
Director of Marmoline Business Unit, Nordia S.A