

L' AQUA PAINT

HIGH QUALITY WATER BASED ENAMEL PAINT

Description : Odourless, new technology water based enamel paint, for indoor/ outdoor use.

Usages: It is applied on wood, metal (aluminium, galvanized metal sheets etc.), gypsumboards or PVC. Suitable for doors, windows, wardrobes and cupboards, walls, roofs etc, and for any metal or wooden construction. Especially recommended for childrens' rooms, nursery schools, hospitals, schools etc.



Advantages:

- Easy to apply
- Excellent whiteness and coverage
- Retains its gloss for a long time and it never appears yellowing effects

Packaging /distribution: Available in 750 ml & 2.5 lt metal cans

Storage: Protect from freezing. Store at room temperatures, from 5°C to 35°C.
Seal the container for future use.

Health and safety : Pay attention on the safety instructions marked on the product's packaging. Refer to the product's Safety Data Sheet for further information.
After use, carefully seal the container for future use. Do not dispose the product's residue in the drain or in household garbage. Handle empty packages according to existing legislation.

VOC (Volatile organic compounds): Subject to directive 2004/42/E.C.: VOC class: A/d "Interior/exterior trim and cladding paints for wood and metal (WB)". Limit value for this product: 130 g/l (2010). This product ready for use contains max VOC 129g/l.

TECHNICAL CHARACTERISTICS:

Colours:	Available in glossy or satin texture, in white or transparent base and in an unlimited number of color shades, through DÉCOR TINTING SYSTEM .
Specific gravity:	1.25 - 1.35 gr/ml (ISO 2811)
Viscosity:	180 – 220 s (Ford Cup No 4)
Drying:	1-3 hours
Gloss degree at 60°:	Glossy 75-85%, Satin 35-50%

APPLICATION:

Performance:	10 – 12 m ² / lt
Application mode:	Roller, brush or spray gun
Dilution:	10 - 20% by volume, with water
Instructions for use:	<ul style="list-style-type: none"> • Prepare the application surface, so that it is clean and dry, free of dust, grease or oils, disintegrated parts etc. • Apply first the water based primer MARMOLINE L' AQUA PRIMER and wait until it thoroughly dries. The old painted surfaces must be well sanded down before application. • Stir well and dilute, 10-20% with water • Apply in two layers, using a roller, a brush or a gun. • It is not recommended to use the product in temperatures below 10oC and above 40oC • Immediately after application, clean tools, using warm water and detergent
Recoating:	After 4 – 6 hours

We guarantee the quality of all our products, on the basis of their technical specifications, as described in this technical data sheet. Such guarantee refers only to the product that we deliver for use and not to its application or final result, which largely depends on the experience of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version