

L' AQUA PRIMER

MULTI-PURPOSE WATER BASED PRIMER

Description : Water based, high quality, odourless white primer with technologically advanced composition. For indoor/ outdoor use.

Usages: It provides very good adhesion on wood, metal (aluminium, galvanized metal sheets etc.), gypsumboards or PVC. It is an ideal undercoat for MARMOLINE L' AQUA PAINT water based enamel paint.



Advantages:

- Easy to apply
- Excellent adhesion
- It is free from lead and zinc chromate

Packaging /distribution: Available in 750 ml & 2.5 lt metal cans

Storage: Protect from freezing. Store at room temperatures, from 5°C to 35°C. Seal the container for future use.

Health and safety : Take into account the safety instructions marked on the product's packaging. For further information ask for the product's Safety Data Sheet. After use, carefully seal the container for future use. Do not dispose the product's residue in the drain or in household garbage. Handle empty packages according to existing legislation.

VOC (Volatile organic compounds): Subject to directive 2004/42/E.C.: VOC class: A/d "Interior/exterior trim and cladding paints for wood and metal (WB)". Limit value for this product: 130 g/l (2010). This product ready for use contains max VOC 125g/l.

TECHNICAL CHARACTERISTICS:

Colours:	White
Specific gravity:	1.40 - 1.45 gr/ml (ISO 2811)
Viscosity:	240 – 280 s (Ford Cup No 4)
Drying:	1-3 hours

APPLICATION:

Performance:	8 – 10 m ² / lt
Application mode:	Roller, brush or spray gun
Dilution:	5-10% by volume with water, for porous surfaces (wood, gypsum boards etc). 15-20% by volume for smooth non-porous surfaces (metal, PVC etc).

- Instructions for use:**
- Prepare the application surface, so that it is clean and dry, free of dust, grease or oils, rust, disintegrated parts etc. Metal surfaces should be ungreased with nitro thinner. PVC surfaces should be cleaned with water and detergent.
 - Stir the product well and dilute it according to the application surface
 - Apply using a roller, a brush or a gun. Avoid recoating when it is more than 5-10 minutes after application of the primer, depending on the existing conditions of ambient temperature and humidity.
 - Wait for about 4 – 6 hours before you apply the MARMOLINE L' AQUA PAINT water based enamel paint.
 - It is not suggested to use the product in temperatures below 5°C and above 40°C
 - Immediately after application, clean tools, using warm water and detergent

Recoating: After 4 – 6 hours

We guarantee the quality of all our products, on the basis of their technical specifications, as described in this technical data sheet. Such guarantee refers only to the product that we deliver for use and not to its application or final result, which largely depends on the experience of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version