

## MST 22

### ROOF ADHESION PRIMER

*Excellent adhesion, perfect preparation.*

**Description :** Ready to use resinous primer which provides excellent adhesion of the substrate to the subsequent layers of brushable waterproofing coatings. Stabilizer for concrete surfaces.

**Usages:** Use it as a primer, to achieve proper adhesion of MARMOLINE AQUATA SEAL 100 and AQUATA SEAL 200 HYBRID brushable elastomeric sealants, to surfaces such as concrete, plaster, plasterboards, etc. Stabilizer and anti-dust treatment for concrete surfaces. Coverage 4-6 m<sup>2</sup> /lt



**Advantages:**

- High penetration
- Does not contain organic solvents
- Quick to dry and repaint
- Safe and pleasant to work with

**Packaging /distribution:**

- Plastic containers of 5 kg and 20 kg.
- Palette of 300 kg, 60 containers of 5 kg.
- Palette of 480 kg, 24 containers of 20 kg.

**Storage:** Store in a covered and shady place, in temperatures between + 5 °C to + 30 °C

**Fire behaviour :** Not flammable

**Safety :** May produce an allergic reaction. Safety data sheet available on request.  
VOC: Maximum V.O.C. content: 2.5 g/L (20 °C). EU limit for the product (Category. A. h. WB): 30 g/L (2010)

**APPLICATION:**

**Consumption:**            Approx. 150 - 200 gr/m<sup>2</sup> depending on the absorbency of the substrate.

- Application mode:**
- Before use, clean the substrate from dust, loose material, etc
  - If there are cracks with more than 1 mm width, they should be repaired using MARMOLINE's repair materials
  - Stir well before use.
  - Dilute the primer with water, up to 50%, depending on the absorbency of the application surface.
  - Apply with a paint roller or paintbrush.
  - For very absorbent surfaces, it is recommended to apply a second coat.
  - Application temperature: + 5 °C to + 35 °C.

The above application guidelines are indicative, for the correct use of the product. For more technical details please contact the company's technical department.

*The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version*