

HI SIL ANTIFUNGAL SILICONE SEALANT

It keeps water and humidity away

Description : Antifungal silicone of high quality and adhesiveness. Once it has hardened it is not affected by water or humidity. It cannot be colored.

Usages: It is used for sealing of joints in bathtubs, sinks, aluminium panels, windows etc.

The application surfaces should be dry and clean. It cannot withstand temperatures ranging from – 50°C to +160°C



Packaging /distribution : Plastic cartridges of 280 ml

Storage: In a sealed cartridge, it is preserved for 12 months from its production date

Technical specifications:

<p style="font-size: 2em; font-weight: bold;">CE</p> <p>14 1292</p> <p>DoP: 057-MARMO-CPR</p>
<p>NORDIA S.A. 364 Kifissias Av., 15233 Chalandri, Athens/ Greece</p>
<p>MARMOLINE HI SIL SEALANT FOR SANITARY JOINTS EN 15651-3: XS1</p>

We guarantee the quality of all our products, on the basis of their technical specifications, as described in the technical data sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depend on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version