

Unique identification code of the product: MARMOLINE SV 60

Type: One coat white plaster

It refers to all batches of MARMOLINE SV 60, produced after the issue of the present declaration

Intended use /es: One coat plaster for internal or external use (OC/CSII/ W_{c1})

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225

Manufacturing plant: 1st km Malakasas – Markopoulou Road, 19011 Malakasa, Attica, Greece

Systems of AVCP: 4

Harmonized standards: EN 998-1:2016

Notified body/ies: -

Declared performance /s:

Essential characteristics	Performance	Harmonised technical spec.
Capillary water absorption:	W _{c1}	EN 998-1:2016 – Table 2 - L5 EN 1015-18
Water vapour diffusion coef.:	$\mu=5/20$	EN 998-1:2016 – Table 2 - L8 EN 1015-19
Adhesion after weathering cycles :	0.3 N/mm ² (FPa)	EN 998-1:2016 – Table 2 - L3 EN 1015-12
Water permeability after 48 h:	< 1 ml /cm ²	EN 998-1:2016 – Table 2 - L7 EN 1015-21
Thermal conductivity:	$\lambda_{10,dry} = 0.37$ W/mK (tab. mean value; P= 50%)	EN 998-1:2016 – Table 2 - L2 EN 1015-11
Reaction to fire:	Class A1 (without testing – organic content < 1,0% - 96/603/EC)	EN 998-1:2016 – 5.2.3.2 & Table 2 - L3, L5
Dangerous substances:	See product's SDS	EN 998-1:2016 – 5.3.4 & Table 2 - L13

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Malakasa, 21/1/2025

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211319
364 KIFISSIAS AVENUE
HALANDRI, 15233 - ATHENS GR
TEL. 0030 - 210 - 68 96 480
FAX. 0030 - 210 - 68 53 410

Dimitrios Poulakidas
R&D-QC manager /Mortars