

L' AQUA PAINT

High quality water based enamel paint

DESCRIPTION

Odourless, water based enamel paint, for indoor/ outdoor use.

APPLICATION FIELDS

It is applied on wood, metal (aluminium, galvanized metal sheets etc.), gypsumboards or PVC. Suitable for doors, windows, wardrobes and cupboards, walls, roofs etc, and for any metal or wooden construction. Especially recommended for childrens' rooms, nursery schools, hospitals, schools etc

CHARACTERISTICS/ ADVANTAGES

- Easy to apply
- Excellent whiteness and coverage
- Retains its gloss for a long time and it never appears yellowing effects

PRODUCT INFORMATION

Packaging: 750 ml & 2.5 lt metal cans

Storage: Protect from freezing. Store at room temperatures, from 5°C to 35°C. Seal the container for future use

TECHNICAL CHARACTERISTICS

Density: 1.25 - 1.35 gr/ml (ISO 2811)

Viscosity: 180 – 220 s (Ford Cup No 4)

Gloss degree at 60°: Glossy 75-85%, Satin 35-50%

Colours: Available in glossy or satin texture, in white or transparent base and in an unlimited number of color shades, through DÉCOR TINTING SYSTEM

APPLICATION INFORMATION

Performance: 10 – 12 m² /lt

Dilution: 10 - 20% by volume, with water

Application mode: Roller, brush or spray gun.

Drying: 1 – 3 hours.

Recoating: After 4 – 6 hours

HEALTH, SAFETY & ENVIROMENTAL PROTECTION

Subject to directive 2004/42/E.C.: VOC class: A/d "Interior/exterior trim and cladding paints for wood and metal (WB)". Limit value for this product: 130 g/l (2010). This product ready for use contains max VOC 129g/l. Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of

which are available on the company's website <https://marmoline.gr/> or upon request

APPLICATION INSTRUCTIONS

- Prepare the application surface, so that it is clean and dry, free of dust, grease or oils, disintegrated parts etc.
- Apply first the water based primer MARMOLINE L' AQUA PRIMER and wait until it thoroughly dries. The old painted surfaces must be well sanded down before application.
- Stir well and dilute, 10-20% with water
- Apply in two layers, using a roller, a brush or a gun.
- It is not recommended to use the product in temperatures below 10oC and above 40oC
- Immediately after application, clean tools, using warm water and detergent

LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in the Declaration of Performance (CE) and this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. All data stated in this Technical Data Sheet are based on laboratory tests. The really measurable data might differentiate due to conditions that are not subject to our control. The recommendations and implementation

instructions must be considered by the user as indicative, and always with given that the product has been traded and traded and stored according to its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.