

RUST OFF

Fast-drying anti-corrosive primer

DESCRIPTION

High strength, fast-drying anti-corrosive primer for metal surfaces.

Based on synthetic resins, it achieves excellent adhesion.

APPLICATION FIELDS

As an undercoat for metal surfaces, it provides long term protection against rust and withstands the roughest conditions.

CHARACTERISTICS/ ADVANTAGES

- It is easy to work with and dries quickly
- It can be applied with spray gun, roller or brush
- It is free from lead and zinc chromate

PRODUCT INFORMATION

Packaging: 750 ml & 2.5 lt metal cans

Storage: Protect from freezing. Store at room temperatures, from 5°C to 35°C. Seal the container for future use

TECHNICAL CHARACTERISTICS

Density: 1.40 - 1.55 gr/ml (ISO 2811)

Viscosity: 280 – 320 s (Ford Cup No 4)

Gloss degree at 60°: Matte

Colours: Gray and brown

APPLICATION INFORMATION

Performance: 8 – 10 m² /lt

Dilution:

Application with brush or roller: dilute up to 3% with white spirit or brush thinner.

Application with spay gun: dilute up to 3% with spray gun thinner .

Application mode: Roller, brush or spray gun.

Drying: 15 min (touch) & 1-2 hours (dry through)

Recoating: After 6 - 8 hours

HEALTH, SAFETY & ENVIROMENTAL PROTECTION

Subject to directive 2004/42/E.C.: VOC class: "One- pack performance coatings (SB) (A/i)". Limit value for this product: 500 g/l (2010). This product ready for use contains max V.O.C. 499g/l.

Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website <https://marmoline.gr/> or upon request

APPLICATION INSTRUCTIONS

- Prepare the application surface, so that it is clean and dry, free of dust, grease or oils, disintegrated parts etc.
- Ensure good ventilation of the application area and wear appropriate protective means.
- Stir well the product and dilute it according to the application mode
- Apply the product, paying particular attention to difficult areas (corners, cavities etc.)
- It is not suggested to use the product in temperatures below 5°C and above 40°C
- Remove from the tools the product that is left over, before cleaning them with solvent.

LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in the Declaration of Performance (CE) and this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on

the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. All data stated in this Technical Data Sheet are based on laboratory tests. The really measurable data might differentiate due to conditions that are not subject to our control. The recommendations and implementation instructions must be considered by the user as indicative, and always with given that the product has been traded and traded and stored according to its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.