

Unique identification code of the product: MARMOLINE AQUATA 240

Cementitious brushable waterproofing mortar

It refers to all batches of MARMOLINE AQUATA 240, produced after the issue of the present declaration

Intended use /es: Protection of concrete surfaces - Coating - moisture control

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225

Manufacturing plant: 1st km Malakasas – Markopoulou Road, 19011 Malakasa, Attica, Greece

Systems of AVCP: System 2+, System 4 (reaction to fire)

Harmonized standards: EN 1504-2:2004 - Principles 2.2 (C), 8.2 (C)

Notified body/ies: TUV AUSTRIA HELLAS (0906)

Declared performance /s:

Essential characteristics	Performance	Harmonised technical spec.
Water vapour permeability:	$S_D < 5 \text{ m (class I)}$	EN 1504-2:2004, table 1 [2 – 2.2(c)], table ZA.1e & §5.2 , table 5 (7) EN ISO 7783-2
Capillary absorption:	$w \leq 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	EN 1504-2:2004, table 1 [2 – 2.2(c)], table ZA.1e & §5.2 , table 5 (8) EN 1062-3
Adhesion strength:	$\geq 1.0 \text{ N/mm}^2$	EN 1504-2:2004, table 1 [2 – 2.2(c)], table ZA.1e & §5.2 , table 5 (15) EN 1542
Reaction to fire:	F	EN 1504-2:2004, table ZA.1d & §5.2 , table 5 (16) & §5.4
Dangerous substances:	Complies with §5.3	EN 1504-2:2004, table ZA.1d & §5.3

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Malakasa, 5/9/2024

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211819
364 KIFISSIAS AVENUE
CHALANDRI, 15233 - ATHENS, GR
TEL. 0030 - 210 - 6896480
FAX: 0030 - 210 - 6853440

Vivi Dilaveri
Director of Marmoline Business Unit, Nordia S.A.