## **DECLARATION OF PERFORMANCE**



under regulation (EU) No 305/2011 and the amendment of Annex III, (EU) No 574/2014



## 058 MARMO-CPR

Unique identification code of the product - type: MARMOLINE CONNECT

Acrylic based sealant

It refers to all batches of MAMROLINE CONNECT, produced after the issue of the present declaration

Intended use /es:

sealing material EN 15651-1: F-EXT-INT (class 12.5 P)

Manufacturer:

NORDIA S.A., 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225

**System of AVCP:** 3

Harmonized standard: EN 15651-1:2012

Notified body/ies: Tecnalia Research & Innovation (1292)

**Declared performance /s:**Conditioning: Procedure A (ISO 8339)

Essential characteristics	Declared performance	Standard
Reaction to fire	Class E	EN 15651-1
Release of chemicals	None (see product's SDS )	
Water Tightness & air tightness as determined by:		
Resistance to flow	<u>&lt;</u> 3mm	
Loss of volume	<u>≤</u> 45%	
Determination of tensile properties after immersion in water (23°C)	<u>≥</u> 25%	
Durability	Pass	

## Appropriate technical documentation:

Tecnalia Research & Innovation (1292), report No 089110-a, 14\_08336-1-a, 14\_08336-2-a DoP ELASTOT. – ACRYL. 30/6/2020

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Polydendri, 1/6/2023

QUARRYING AND INDUSTRIAL AND COMMERCIAL CO.S.A. VAT: EL 999211319
364 KIRISSAS AVENUE
HALANDRI 156238 ATHENS CR. TEL. 0031 210 6896 180

Vivi Dilaveri Director of Marmoline Business Unit, Nordia S.A.