

DECLARATION OF PERFORMANCE

NORDIA

under regulation (EU) No 305/2011
and the amendment of Annex III, (EU) No 574/2014
No: 266 MAR-CPR



Unique identification code of the product: MARMOLINE KL 101

It refers to all batches of MARMOLINE KL 101, produced after the issue of the present declaration

Intended use /es: Thin layer masonry mortar (T)

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel +302295022225

Manufacturing plant: 1st km Provincial Road Malakasas - Markopoulou, 19011 Malakasa, Attica, Greece

Systems of AVCP: System 2+

Harmonized standards: EN 998-2:2016

Notified body/ies: TÜV HELLAS (TÜV NORD) (0654)

Declared performance /s:

Essential characteristics	Performance	Harmonised technical spec.
Compressive strength	M10	EN 998-2:2016 § 5.4.1 EN 1015-11
Shear strength	0.30 N/mm ²	EN 998-2:2016 § 5.4.2.1.b Annex.C (tabulated)
Reaction to fire	Class A1	EN 998-2:2016 § 5.4.8 (without testing – organic content< 1.0%)
Water absorption	≤ 0.5 kg/m ² min ^{0.5}	EN 998-2:2016 § 5.4.3 EN 1015-18
Water vapour permeability (μ)	5/20	EN 998-2:2016 § 5.4.4 EN 1745:2012, table A12 (tabulated)
Thermal conductivity	0.41 W/mK (λ _{10,dry} P=50%)	EN 998-2:2016 § 5.4.6 EN 1745:2012, table A12 (tabulated)
Chloride content	≤ 0.1%	EN 998-2:2016 § 5.5.2 EN 1015-17
Workable life	240 min	EN 998-2:2016 § 5.2.1 EN 1015-9
Maximum grain size	1 mm	EN 998-2:2016 § 5.5.2
Correction time	5 min	EN 998-2:2016 § 5.5.3 EN 1015-9
Durability	NPD	EN 998-2:2016 § 5.4.7
Dangerous substances	See product's SDS	EN 998-2:2016 § 5.4.9

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Malakasa, 4/8/2026

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211319
364 KIFISSIAS AVENUE
HALANDRI, 15233 - ATHENS GR
TEL. 0030 - 210 - 68 96 480
FAX. 0030 - 210 - 68 53 410

Dimitrios Poulakidas
R&D-QC manager /Mortars