

## FLYING COLOURS EXTERIOR

### Acrylic paint for exterior use

#### DESCRIPTION

Acrylic paint for exterior use. It spreads easily, producing a matt, water resistant and vapour permeable surface.

#### APPLICATION FIELDS

Suitable for any surface made of plaster, concrete, gypsum board. Also for old, previously painted surfaces

#### CHARACTERISTICS/ ADVANTAGES

- Easy to use
- Excellent coverage
- Strong adhesion
- Resistant to bad weather conditions
- Long lasting
- Prevents mould
- Allows vapour permeability of the surface
- Washable with a soft sponge.

#### PRODUCT INFORMATION

**Packaging:** 750 ml, 3 lt & 10 lt plastic containers

**Storage:** Keep this product in a shadowed place and avoid exposure to very high temperature or frost (optimum storing temperature: +5°C to

+35°C). Maximum storage time, in intact packaging: 12 months after production date

#### TECHNICAL CHARACTERISTICS

**Density:** 1.46 ± 0.02 kg/ lt

**Colours:** According to colour palette in more than a thousand of shades

#### APPLICATION INFORMATION

**Coverage:** 12 – 13 m<sup>2</sup> /lt

**Dilution:** 5 – 10% with water

#### Application mode:

Roller, brush or spray gun. It can also be applied with a brush, sponge or a cloth, to create specific texture.

#### Drying:

In touch: 50 – 60 minutes, depending on the weather conditions.

**2<sup>nd</sup> layer:** After 3 – 3.5 hours

## HEALTH, SAFETY & ENVIROMENTAL PROTECTION

VOC: Maximum V.O.C. content: 39 g/L (20 °C). EU limit for the product (Cat. A. c. WB): 40 g/L (2010). Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website <https://marmoline.gr/> or upon request

## APPLICATION INSTRUCTIONS

- Make sure that the surfaces are clean and free of grease.
- Remove loose parts or peelings of previous paint.
- New surfaces or surfaces that were in a poor condition and were repaired /covered with stucco, should be first primed with the MARMOLINE MST 11 primer, either undiluted or diluted by up to 30% with water
- Stir FLYING COLOURS well before use.
- You may dilute it by adding 5-10% water.
- Apply in 2 layers

## LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in the Declaration of Performance (CE) and this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on the experience and quality of work of each user and on the application conditions. The user is advised to

test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. All data stated in this Technical Data Sheet are based on laboratory tests. The really measurable data might differentiate due to conditions that are not subject to our control. The recommendations and implementation instructions must be considered by the user as indicative, and always with given that the product has been traded and traded and stored according to its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.