

MST 11

Acrylic water based primer

DESCRIPTION

Transparent acrylic water-based primer for the preparation of surfaces before plastering or painting. It can be used on interior and exterior absorbent surfaces. It provides better adhesion of the next coat of plaster or paint. It prevents flaking. High-tech composition, it deeply penetrates the surface of the substrate and provides better adhesion.

With EUROFINS Indoor Air Comfort Gold certification which ensures that the product meets the strictest European regulations regarding VOC emissions. The product is also accompanied by an Environmental Product Declaration (EPD) regarding the environmental impact during its life cycle (EPD registration number: IES-0014663).

FIELDS OF APPLICATION

Apply to old or new surfaces, such as plaster or stucco walls. It reinforces and stabilizes porous surfaces to be painted with emulsion or acrylic paint. Due to the decrease in surface absorbance, the time required for

painting is reduced and the paint coverage is increased. It is also used as a primer for surfaces to be coated with a colored render, so as to reduce the absorbency of the substrate and let the colored render dry uniformly.

CHARACTERISTICS/ADVANTAGES

- Odourless
- Does not contain organic solvents
- Safe and easy to use
- Dries quickly
- Allows the surface to breath, since it forms a membrane with micropores
- High penetration ability

PRODUCT INFORMATION

Packaging	Plastic containers 5kg, 10kg & 20kg Palette of 300 kg, 60 containers of 5 kg. Palette of 400 kg, 40 containers of 10 kg. Palette of 480 kg, 24 containers of 20 kg.
Storage conditions	In the original, closed, sealed and indestructible package, protected from direct sunlight and frost and at temperatures from +5°C to + 30°C.
Lifetime	12 months from production date
Density	1.0 kg/l

APPLICATION INFORMATION

Environmental temperature	from + 5 °C to + 35 °C
Consumption	Approx. 1 kg per 10 to 15 m ² depending on the absorbency of the application surface

APPLICATION INSTRUCTIONS

Stir before use.

Apply with a paint roller or paintbrush, diluted with water (30% - 100%), depending on the absorbency of the application surface.

For very absorbent surfaces, the recommended dilution with water is 30% - 50%.

Apply with a roller or brush.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION

VOC: Maximum V.O.C. content: 29 g/L (20 °C).
EU limit for the product (Category. A. h. WB): 30 g/L (2010). Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website www.marmoline.gr or upon request.

LEGAL NOTICES

We guarantee the quality of the product, in terms of its technical specifications, as presented in the technical data sheet. This guarantee is strictly only for the available product and in no case the final result from its application, which depends to a large extent on the experience and quality of work of each user, as well as the conditions of application.

It is recommended that the user apply the product on a small scale and after making sure of the result, then use it in his project. Publication of this technical data sheet supersedes any previous version.

MARMOLINE reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.