

Unique identification code of the product: MARMOLINE BP 115

Type: Rendering /plastering mortar for internal or external use

It refers to all batches of MARMOLINE BP 115, produced after the issue of the present declaration

Intended use /es: One coat plaster/render (OC/CSII/W_{c2})

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece. Manufacturing plant: 1st klm Country road Markopoulou-Oropou, 19014 Polydendri Attikis/ Greece, tel: +302295022225

Systems of AVCP: 4

Harmonized standards: EN 998-1:2016

Notified body/ies: -

Declared performance /s:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical spec.</i>
Capillary water absorption:	W _{c2}	EN 998-1:2016 – Table 2 - L5 EN 1015-18
Water vapour diffusion coef.:	μ=5/20	EN 998-1:2016 – Table 2 - L8 EN 1015-19
Adhesion after weathering cycles :	0.6 N/mm ² (FPc)	EN 998-1:2016 – Table 2 - L3 EN 1015-12
Water permeability after 48 h:	< 1 ml /cm ²	EN 998-1:2016 – Table 2 - L7 EN 1015-21
Thermal conductivity:	λ _{10,dry} = 0.33 W/mK (tab. mean value; P= 50%)	EN 998-1:2016 – Table 2 - L2 EN 1015-11
Reaction to fire:	Class A1 (without testing – organic content < 1,0% - 96/603/EC)	EN 998-1:2016 – 5.2.3.2 & Table 2 - L3, L5
Dangerous substances:	See product’s SDS	EN 998-1:2016 – 5.3.4 & Table 2 - L13

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Polydendri, 1/6/2023

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211319
364 KIFISSIAS AVENUE
CHALANDRI, 15233, ATHENS, GR
TEL. 0030 - 210 - 68 53 480
FAX. 0030 - 210 - 68 53 410

Vivi Dilaveri
Director of Marmoline Business Unit, Nordia S.A.