

MST 22

Roof adhesion primer

DESCRIPTION

Ready to use resinous primer which provides excellent adhesion of the substrate to the subsequent layers of brushable waterproofing coatings. Stabilizer for concrete surfaces.

Coverage 4-6 m² /lt

FIELDS OF APPLICATION

Use as primer to achieve proper adhesion of MARMOLINE AQUATA SEAL 100 and AQUATA SEAL 200 HYBRID brushable elastomeric sealants, to surfaces such as concrete, plaster, plasterboards, etc.

Stabilizer and anti-dust treatment for concrete surfaces.

CHARACTERISTICS/ADVANTAGES

- High penetration
- Does not contain organic solvents
- Quick to dry and repaint
- Safe and pleasant to work with.

PRODUCT INFORMATION

Packaging

Plastic containers of 5 kg and 20 kg.
Palette of 300 kg, 60 containers of 5 kg.
Palette of 480 kg, 24 containers of 20 kg

Storage conditions

In the original, closed, sealed and indestructible package, protected from direct sunlight and frost and at temperatures from +5°C to + 30°C.

Lifetime

12 months from production date

APPLICATION INFORMATION

Environmental temperature

from + 5 °C to + 35 °C

Consumption

150 - 200 gr/m² depending on the absorbency of the substrate

APPLICATION INSTRUCTIONS

- Before use, clean the substrate from dust, loose material, etc
- If there are cracks with more than 1 mm width, they should be repaired using MARMOLINE's repair materials
- Stir well before use.
- Dilute the primer with water, up to 50%, depending on the absorbency of the application surface.
- Apply with a paint roller or paintbrush
- For very absorbent surfaces, it is recommended to apply a second coat.

application, which depends to a large extent on the experience and quality of work of each user, as well as the conditions of application. It is recommended that the user apply the product on a small scale and after making sure of the result, then use it in his project. Publication of this technical data sheet supersedes any previous version. MARMOLINE reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

HEALTH, SAFETY & ENVIRONMENTAL PROTECTION

VOC: Maximum V.O.C. content: 29 g/L (20 °C).
EU limit for the product (Category. A. h. WB): 30 g/L (2010). Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website www.marmoline.gr or upon request.

LEGAL NOTICES

We guarantee the quality of the product, in terms of its technical specifications, as presented in the technical data sheet. This guarantee is strictly only for the available product and in no case the final result from its