

UNI PAINT ACRYL

Acrylic cement paint

DESCRIPTION

Acrylic cement paint suitable for exterior use. It is easily workable and has excellent leveling properties. It allows surface to “breathe”.

APPLICATION FIELDS

Due to its special composition, it is highly resistant to alkalis, on new or re-painted surfaces and in adverse weather conditions. It offers great coverage and unrivaled performance

CHARACTERISTICS/ ADVANTAGES

- Easy to use
- Odourless
- Excellent coverage and resistance to adverse weather conditions
- Allows vapour permeability of the surface
- Washable with a soft sponge

PRODUCT INFORMATION

Packaging: 750 ml, 3 lt & 9 lt plastic containers

Storage: Keep this product in a shadowed place and avoid exposure to very high temperature or frost (optimum storing temperature: +5°C to +35°C). Maximum storage time, in intact packaging: 12 months after production date

TECHNICAL CHARACTERISTICS

Density: 1.5 kg/ lt

Colours: Available in two basic colors, white and gray, and in more than 1700 shades, using the coloring system of MARMOLINE

APPLICATION INFORMATION

Coverage: 13 – 14 m² /lt

Dilution: 5 – 10% with water

Application mode:

Roller, brush or spray gun.

Drying:

In touch: 50 – 60 minutes, depending on the weather conditions.

2nd layer: After 3 – 3.5 hours

HEALTH, SAFETY & ENVIROMENTAL PROTECTION

VOC: Maximum V.O.C. content: 39 g/L (20 °C). EU limit for the product (Cat. A. c. WB): 40 g/L (2010). Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website <https://marmoline.gr/> or upon request

APPLICATION INSTRUCTIONS

- Make sure that the surfaces are clean and free of grease.
- Remove loose parts or peeling of the old paint
- For puttying and leveling of the surfaces, use the acrylic stucco MARMOLINE STUCCO BIANCO or the acrylic putty, MARMOLINE STUCCO PASTE.
- On new surfaces or surfaces that were in poor condition and repaired, apply first the MARMOLINE MST 11 primer, undiluted or diluted up to 30% with water
- Stir UNI PAINT ACRYL well before use
- You may dilute the product with 5 – 10% water
- Apply in 2 layers

its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.

LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in the Declaration of Performance (CE) and this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. All data stated in this Technical Data Sheet are based on laboratory tests. The really measurable data might differentiate due to conditions that are not subject to our control. The recommendations and implementation instructions must be considered by the user as indicative, and always with given that the product has been traded and traded and stored according to