

TCL 100

CLEANER FOR TILES, GROUTS, GRANITES, NATURAL & ARTIFICIAL STONES

Fast and effective cleaning.

Description : Very strong and condensed cleaner, suitable for ceramic tiles - cotto - natural and artificial granite tiles, tile joints, decorative stones, etc. It effectively cleans residues of cement, plasters, joint fillers from various works. It is an indispensable tool for all users. Suitable for cleaning dirt caused from wear, coffee stains, oils, rust, stains coming from watering of flower-pots, etc.

Usages : It is suitable for

- All types of absorbent and non-absorbent ceramic tiles, such as cotto, terracotta, ceramic glazed tiles, cement pavement tiles, gardens etc.
- Cementitious grouts of marbles and tiles, restoring the original color of grout
- Natural stones and setts of stones, pebbles etc.
- Most types of artificial stones
- Horizontal and vertical surfaces such as balconies, garden walkways, sidewalks, window sills, walls clad with stones etc.

In combination with waterproofing liquid, provides a long term protection.

Remarks: Due to the different nature of each material, it is advised to make a compatibility test, on a small section of the surface, prior to final application. Coloured grouts should be handled with extra care because the cleaning may result in whitening their colour. It is not suitable for limestones.

Advantages:

- Instant and effective action.
- Suitable for many applications.
- Revitalizes the look of surfaces.
- Does not change the look of absorbent tiles.
- Indoor and outdoor use.
- Easy to apply.

Packing : Plastic containers of 1lt and 4 lt.

Storage: Containers must be stored in dry areas at a temperature from +5°C to +35°C and protected from sunlight and are preserved for at least 24 months from the date of production.

Fire behaviour : Not flammable

Health and safety : Corrosive product (causes burns), and irritant. Read carefully the instructions on the packaging and Safety Data Sheet



FEATURES:

| | |
|--------------------------|--------------------|
| Form: | Transparent liquid |
| Odour: | Acidic |
| Specific gravity: | 1 gr /ml, 25°C |

APPLICATION:

Consumption: Approx. 1 lt per 5 to 6 m².

Application mode:

- TCL 100 is very strong, so it is recommended to wear protective gloves and goggles.
- To avoid any possible corrosion, it is recommended to perform a trial application on a small part of the surface .
- Remove or cover any sensitive surfaces and items.
- Spread TCL 100 undiluted on the surface and rub with a broom or harsh sponge for 3 - 5 minutes.
- Before the material dries, rinse the surface with clean water while rubbing with the broom.
- If there are persistent stains, you may repeat the process 15 - 20 minutes later
- For small, light you may dilute it by 20% with water.
- It is not recommended for polished marbles.
- Application temperature :+5 °C to +35°C

The above application guidelines are indicative, for the correct use of the product. For more technical details please contact the company's technical department.

The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version