

SUPER PAINT

Elastomeric protective wall paint

DESCRIPTION

Acrylic, elastomeric, high strength protective/waterproofing paint for exterior walls.

APPLICATION FIELDS

It combines the properties of a paint and a water-repellent liquid in one product, by creating an elastic protective membrane.

It is applied on all types of surfaces, such as plaster, concrete, cement board, external thermal insulation composite systems.

The flexible film covers and hides capillary cracks, making uniform pinhole-free jobs easier and faster to achieve. It incorporates a MARMOLINE.

Dirt Pick-Up Resistance (DPR) technology combined with a high solid volume content that provides a longest lasting waterproofing membrane.

CHARACTERISTICS/ ADVANTAGES

- Exceptional hydrophobia (lotus effect).
- Ensures waterproofing - watertightness of the brickwork
- Fiber reinforced
- Seals and bridges capillaries and microcracks
- Self-cleaning. Barrier against atmospheric pollutants
- Excellent resistance to UV rays
- Washable with a soft sponge

PRODUCT INFORMATION

Packaging: 750 ml, 5 lt & 10 lt plastic containers

Storage: Keep this product in a shadowed place and avoid exposure to very high temperature or frost (optimum storing temperature: +5°C to +35°C). Maximum storage time, in intact packaging: 12 months after production date

TECHNICAL CHARACTERISTICS

Density: 1.46 ± 0.02 kg/ lt

Colours: According to colour palette in more than a thousand of shades

APPLICATION INFORMATION

Coverage: Approx. 10 m²/lt per layer, according to the substrate

HEALTH, SAFETY & ENVIROMENTAL PROTECTION

VOC: Maximum V.O.C. content: 39 g/L (20 °C). EU limit for the product (Cat. A. c. WB): 40 g/L (2010). Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website <https://marmoline.gr/> or upon request

APPLICATION INSTRUCTIONS

- Stir before use.
- New surfaces must first be primed with the water-based primer MARMOLINE MST 11, undiluted or diluted up to 30% with water, depending on the surface.
- For fine cracks, and cracks larger than 0.5 mm, first fill the crack properly.
- Apply the next layer after 6-8 hours.
- Application temperature: +5°C to 35°C.

result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.

LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in the Declaration of Performance (CE) and this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. All data stated in this Technical Data Sheet are based on laboratory tests. The really measurable data might differentiate due to conditions that are not subject to our control. The recommendations and implementation instructions must be considered by the user as indicative, and always with given that the product has been traded and traded and stored according to its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final