

VELVET PRIMER

PRIMER FOR THE DECORATIVE CEMENT-BASED FINISHING SCREED VARNISH

For strong adhesion

Description: Transparent, brushable water-based primer.

Usages : It improves the adhesion of the water-based varnish VELVET LIQUID S, on absorbent surfaces, such as the decorative cement-based finishing screed.

Advantages:

- High penetration ability
- Safe and easy to work with
- Organic solvent-free



Packaging : Available in 5 lt plastic tanks & 1 lt plastic bottles

Storage: Store the product in a shadowed place and avoid exposure to very high temperature or frost (optimum storing temperature: +5°C to +35°C). Maximum storage time in intact packaging: 12 months after production date.

Fire behaviour : Not flammable

Safety : VOC class: "Binding primers". VOC limit = 30 gr/lit.
Max VOC of product ready to use: <5 gr/lit.

Consumption: 150 - 200 ml /m², depending on the absorbency and the flatness of the surface

Οδηγίες χρήσεως:

- Clean the substrate before use
- Stir the VELVET PRIMER well
- Apply using the appropriate roller

Εγγυούμαστε για την ποιότητα του προϊόντος, σε ότι αφορά τις τεχνικές προδιαγραφές του, όχι όμως για το τελικό αποτέλεσμα από την εφαρμογή του. Αυτό εξαρτάται σε μεγάλο βαθμό από την εμπειρία του εκάστοτε χρήστη, καθώς και τις συνθήκες εφαρμογής. Συνιστάται γι' αυτό, στον χρήστη, να εφαρμόζει το προϊόν δοκιμαστικά, σε μικρή κλίμακα, και αφού βεβαιωθεί για το αποτέλεσμα, τότε να το χρησιμοποιεί στο έργο του. Η έκδοση του παρόντος τεχνικού φυλλαδίου ακυρώνει κάθε προηγούμενη έκδοση αυτού.