# **DECLARATION OF PERFORMANCE**



under regulation (EU) No 305/2011 and the amendment of Annex III, (EU) No 574/2014 No: 011 MARMO-CPR



## Unique identification code of the product: MARMOLINE UNIVERSAL

Type: Cementitious adhesive for tiles (C1) with reduced slip (T) and extended open time (E). It refers to all batches of MARMOLINE UNIVERSAL, produced after the issue of the present declaration

### Intended use /es: Tile adhesive

#### Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225 Manufacturing plant: 1<sup>st</sup> km Malakasas – Markopoulou Road, 19011 Malakasa, Attica, Greece

#### Systems of AVCP: 3

*Harmonized standards*: EN 12004:2007 + A1:2012 *Notified body/ies:* 

#### Declared performance /s:

Essential characteristics	Performance	Harmonised technical spec.
Initial tensile adhesion strength (after 28 days):	<u>&gt;</u> 0.5 N/mm <sup>2</sup>	
Tensile adhesion strength after heat ageing :	<u>&gt;</u> 0.5 N/mm <sup>2</sup>	EN 12004:2007+A1 § 5.4 table 5 EN 1348
Tensile adhesion strength after water immersion :	<u>&gt;</u> 0.5 N/mm <sup>2</sup>	
Tensile adhesion strength after freeze/thaw cycles:	<u>&gt;</u> 0.5 N/mm <sup>2</sup>	
Reaction to fire:	Class A1 (without testing – organic content < 1,0% - 96/603/EC)	EN 12004:2007+A1 § 4.4 EN 13501-1
Release of dangerous substances:	See product's SDS	EN 12004:2007+A1 § 4.5

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Malakasa, 21/1/2025

VORDI RRYING AND COMMERCIAL 999 RIFISSIAS 152

Dimitrios Poulakidas R&D-QC manager /Mortars