

Unique identification code of the product: MARMOLINE PYRO PRO

Type: Refractory mortar

It refers to all batches of MARMOLINE PYRO PRO, produced after the issue of the present declaration

Intended use /es: Masonry mortar

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225

Manufacturing plant: 1st klm Country road Markopoulou-Oropou, 19014 Polydendri Attikis/ Greece

Systems of AVCP: 4

Harmonized standards: EN 998-2:2016

Notified body/ies: -

Declared performance /s:

Essential characteristics	Performance	Harmonised technical spec.
Proportion of constituents:	Cement: 28% Aggregates: 71.3%	EN 998-2:2016 § 5.3
Contents of chloride:	0.02% Cl	EN 998-2:2016 § 5.2.2 EN 1015-17
Reaction to fire:	Class A1 (without testing – organic content < 1,0% - 96/603/EC)	EN 998-2:2016 § 5.4.8 EN 13501-1
Water absorption:	0.22 kg / (m ² . min ^{0,5})	EN 998-2:2016 § 5.4.3 EN 1015-18
Water vapour permeability:	μ = 15/35	EN 998-2:2016 § 5.4.4 EN 1745
Thermal conductivity /density:	(λ _{10,dry}) = 0.83 W/mK (tabulated mean value P= 50%)	EN 998-2:2016 § 5.4.6 EN 1745
Durability (against freeze/thaw, in the intended place of use):	NPD	EN 998-2:2016 § 5.4.7

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Polydendri, 1/6/2023

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211819
364 KIFISSIAS AVENUE
CHALANDRI, 15233 - ATHENS, GR
TEL. 0030 - 210 - 68 96 480
FAX. 0030 - 210 - 68 53 440

Vivi Dilaveri
Director of Marmoline Business Unit, Nordia S.A.