

MST 11

ACRYLIC WATER-BASED PRIMER

Easy, fast, strong primer for all purposes

Description : Transparent acrylic water-based primer for the preparation of surfaces before plastering or painting. It can be used on interior and exterior absorbent surfaces. It provides better adhesion of the next coat of plaster or paint. It prevents flaking. High-tech composition, it deeply penetrates the surface of the substrate and provides better adhesion.

Usages: Apply to old or new surfaces, such as plaster or stucco walls. It reinforces and stabilises porous surfaces to be painted with emulsion or acrylic paint. Due to the decrease in surface absorbance, the time required for painting is reduced, and the paint coverage is increased. It is also used as a primer to the surfaces to be coated with a colored plaster, so as to reduce the absorbency of the substrate and let the colored plaster dry evenly.



Product information: Density: 1 kg/ lt

Advantages:

- Does not contain organic solvents
- Odourless
- Safe and pleasant to work with
- Quick to dry and repaint
- Breathable; it forms a membrane with micro-pores
- High penetration of the surface

Packaging /distribution:

- Plastic containers of 5 kg, 10 kg and 20 kg.
- Palette of 300 kg, 60 containers of 5 kg.
- Palette of 400 kg, 40 containers of 10 kg.
- Palette of 480 kg, 24 containers of 20 kg.

Storage: Store in a covered and shady place, in temperatures between + 5 °C to + 30 °C

Fire behaviour : Not flammable

Safety : VOC class: "Binding primers". VOC limit: 30 gr/lt.
Max VOC of product ready to use: 29 gr/lt.

Specifications : **European Guideline ETAG 004**, as a part of MARMOLINE MONOSIS ETICS

APPLICATION:

Consumption: Approx. 1 kg per 10 to 15 m².

- Application mode:**
- Stir before use.
 - Apply with a paint roller or paintbrush, dissolved in water (30% - 100%), depending on the absorbency of the application surface.
 - For very absorbent surfaces, the recommended dilution in water is 30% - 50%.
 - Application temperature: + 5 °C to + 35 °C.

The above application guidelines are indicative, for the correct use of the product. For more technical details please contact the company's technical department.

The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version