

STUCCO PASTE

White acrylic putty for constructions

DESCRIPTION

Ready to use, acrylic, flexible putty, in the form of white paste.

APPLICATION FIELDS

It can easily fill cracks and joints in concrete or plaster walls, gypsum boards, etc.

CHARACTERISTICS/ ADVANTAGES

- Very good adhesion and durability.
- Wide coverage.
- It dries quickly - it does not crack
- Surface easily rubbed with a sandpaper – Smooth and durable result.
- It can be painted with any emulsion or enamel paint

PRODUCT INFORMATION

Packaging Available in 800 gr plastic container

Storage: Store the product in a shadowed place and avoid exposure to very high temperature or frost (optimum storing temperature: +5°C - +35°C). Maximum storage time in intact packaging: 12 months after production date.

APPLICATION

Make sure that the surface is clean and free of loose material or grease. Smooth cracks and, if necessary, apply a layer of the MARMOLITE MST 11 primer.

Apply the STUCCO PASTE using a spatula

HEALTH, SAFETY & ENVIROMENTAL PROTECTION

Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website <https://marmoline.gr/> or upon request.

LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. The recommendations and implementation instructions must be considered by the user as indicative, and always with given that

the product has been traded and stored according to its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.