

## L' AQUA PRIMER

### High quality water based enamel paint

#### DESCRIPTION

Water based, high quality, odourless white primer with technologically advanced composition. For indoor/ outdoor use.

#### APPLICATION FIELDS

It provides very good adhesion on wood, metal (aluminium, galvanized metal sheets etc.), gypsumboards or PVC. It is an ideal undercoat for MARMOLINE L' AQUA PAINT water based enamel paint

#### CHARACTERISTICS/ ADVANTAGES

- Easy to apply
- Excellent adhesion
- It is free from lead and zinc chromate

#### PRODUCT INFORMATION

**Packaging:** 750 ml & 2.5 lt metal cans

**Storage:** Protect from freezing. Store at room temperatures, from 5°C to 35°C. Seal the container for future use

#### TECHNICAL CHARACTERISTICS

**Density:** 1.40 - 1.45 gr/ml (ISO 2811)  
**Viscosity:** 240 – 280 s (Ford Cup No 4)  
**Colour:** white

#### APPLICATION INFORMATION

**Performance:** 8 – 10 m<sup>2</sup> /lt  
**Dilution:** 5-10% by volume with water, for porous surfaces (wood, gypsum boards etc). 15-20% by volume for smooth non-porous surfaces (metal, PVC etc ).

**Application mode:** Roller, brush or spray gun.

**Drying:** 1 – 3 hours.

**Recoating:** After 4 – 6 hours

#### HEALTH, SAFETY & ENVIRONMENTAL PROTECTION

Subject to directive 2004/42/E.C.: VOC class: A/d “Interior/exterior trim and cladding paints for wood and metal (WB)”. Limit value for this product: 130 g/l (2010). This product ready for use contains max VOC 125g/l. Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website <https://marmoline.gr/> or upon request

## APPLICATION INSTRUCTIONS

- Prepare the application surface, so that it is clean and dry, free of dust, grease or oils, rust, disintegrated parts etc. Metal surfaces should be ungreased with nitro thinner. PVC surfaces should be cleaned with water and detergent.
- Stir the product well and dilute it according to the application surface
- Apply using a roller, a brush or a gun. Avoid recoating when it is more than 5 -10 minutes after application of the primer, depending on the existing conditions of ambient temperature and humidity.
- Wait for about 4 - 6 hours before you apply the MARMOLINE L' AQUA PAINT water based enamel paint.
- It is not suggested to use the product in temperatures below 5oC and above 40oC
- Immediately after application, clean tools, using warm water and detergent

Technical Data Sheet are based on laboratory tests. The really measurable data might differentiate due to conditions that are not subject to our control. The recommendations and implementation instructions must be considered by the user as indicative, and always with given that the product has been traded and traded and stored according to its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.

## LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in the Declaration of Performance (CE) and this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. All data stated in this