

**Unique identification code of the product: MARMOLINE GN 30**

Type: Sprayed mortar for masonry reinforcement

It refers to all batches of MARMOLINE GN 30, produced after the issue of the present declaration

**Intended use /es:** General purpose cement plaster/render (GP /CSIV /W<sub>c</sub>1)

**Manufacturer /Distributor:**

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece. Manufacturing plant: 1st klm Country road Markopoulou-Oropou, 19014 Polydendri Attikis/ Greece, tel: +302295022225

**Systems of AVCP:** 4

**Harmonized standards:** EN 998-1:2016

**Notified body/ies:** -


**Declared performance /s:**

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonised technical spec.</i>
Capillary water absorption:	W <sub>c</sub> 1	EN 998-1:2016 – Table 2 - L5 EN 1015-18
Water vapour diffusion coef.:	μ=15/35	EN 998-1:2016 – Table 2 - L8 EN 1015-19
Adhesion after weathering cycles :	≥ 0.7 N/mm <sup>2</sup> (FPb)	EN 998-1:2016 – Table 2 - L3 EN 1015-12
Thermal conductivity:	λ <sub>10,dry</sub> = 1.17 W/mK (tab. mean value; P= 50%)	EN 998-1:2016 – Table 2 - L9 EN 1745
Durability (against freeze/thaw in the place of use):	NPD	EN 998-1:2016 – 5.2.3.2
Reaction to fire:	Class A1 (without testing – organic content < 1,0% - 96/603/EC)	EN 998-1:2016 – 5.2.3.2 & Table 2 - L3, L5
Dangerous substances:	See product’s SDS	EN 998-1:2016 – 5.3.4 & Table 2 - L13

**The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:**

Polyendri, 1/6/2023

NORDIA S.A.  
QUARRYING AND INDUSTRIAL  
AND COMMERCIAL CO.S.A.  
VAT: EL 9992111319  
364 KIFISSIAS AVENUE  
CHALANDRI 15233 ATHENS GR  
TEL. 0030 - 210 - 68 50 480  
FAX. 0030 - 210 - 68 53 440



Vivi Dilaveri  
Director of Marmoline Business Unit, Nordia S.A.