

BITUPRIMER

BITUMINOUS VARNISH – PRIMER

Strong adhesion for demanding surfaces

Description: Bituminous sealing varnish, with specially processed bitumen and solvents. It shows great adhesiveness to concrete, lightweight concrete, metal, wood, rock, brick or plasterboard surfaces.

Usages : It is used for the sealing and protection of surfaces made of concrete and metal, such as rooms, underground walls, foundations of underground drains, tanks (made of concrete or metal). It is also used as a primer for the attachment of bituminous membranes, diluted by 20% with gasoline. It is affected by petroleum products. It should not be applied on surfaces of products made of polystyrene (expanded or extruded), as it contains organic solvents.



Advantages:

- Suitable for many types of surfaces.
- It dries quickly.
- It creates a protective membrane that is highly resistant to water, diluted acids and alkalines.

Packaging: In metal containers of 1lt, 5lt and 20 lt

Storage: It should be stored in roofed spaces (+ 5°C to + 35°C), away from direct sunlight as well as away from heat and fire sources. In a closed container, in the above-mentioned situations, this product is preserved unaltered for an unlimited time.

TECHNICAL FEATURES:

Form:	Black, thin liquid
Density:	0,90-0,95 gr/cm ³ (ASTM D41)
Dry extract after evaporation:	60-65% (ASTM D41)
Penetrability of the extract at 25°C:	25±5 dmm (ASTM D41)

Softening point of the dry extract:	≥85°C (ASTM D41)
Solubility in trichloroethylene:	>99%

APPLICATION:

Consumption: 0.3 – 0.5 lt /m², per layer, depending on the type and the absorbency of the surface.

Application mode:

- Check surfaces to make sure that they are dry and clean from dirt, oils and rickety materials.
- Stir the product well before use.
- Apply the material using a grass brush, a paintbrush, a roller or a paint sprayer gun.
- For the priming (pre-coating) dilute the material by 20% using gasoline.
- For sealing /waterproofing protection, you only need to apply an extra coating diluted by 10% using gasoline.
- If you want a stronger, longer lasting protective membrane, apply another coating, diluted by 10% with gasoline, once the previous coating has dried completely.
- Surfaces that are exposed to the sun, should be covered after 24 hours, using the bituminous aluminum varnish ALUPASTE for protection of the membrane from the ultraviolet radiation that causes aging.
- Tools should be cleaned immediately after use, by using gasoline

Εγγυόμαστε για την ποιότητα του προϊόντος, σε ότι αφορά τις τεχνικές προδιαγραφές του, όπως αυτές αποτυπώνονται στη δήλωση επίδοσης (CE) και το τεχνικό φυλλάδιο. Η εγγύηση αυτή αφορά αυστηρά και μόνο το προϊόν που διατίθεται, και σε καμία περίπτωση το τελικό αποτέλεσμα από την εφαρμογή του, το οποίο εξαρτάται σε μεγάλο βαθμό από την εμπειρία και την ποιότητα της εργασίας του εκάστοτε χρήστη, καθώς και τις συνθήκες εφαρμογής. Συνιστάται στον χρήστη να εφαρμόζει το προϊόν δοκιμαστικά, σε μικρή κλίμακα, και αφού βεβαιωθεί για το αποτέλεσμα, τότε να το χρησιμοποιεί στο έργο του. Η έκδοση του παρόντος τεχνικού φυλλαδίου ακυρώνει κάθε προηγούμενη έκδοση αυτού.