

### Uni Paint W-XW-T

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Uni Paint W-XW-T

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Liquid paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

NORDIA S.A. 364 Kifisias Av.

15233 Chalandri - Greece

Phone: +30 22950 22225 - Fax: +30 22950 22120

info@marmoline.gr www.marmoline.gr

1.4 Emergency telephone number: +30 210 7793 777 (Greek Poison Info Center)

## **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1 Classification of the substance or mixture:

## CLP Regulation (EC) No 1272/2008:

The product is not classified as hazardous according to CLP Regulation (EC) No 1272/2008.

#### 2.2 Label elements:

## CLP Regulation (EC) No 1272/2008:

## Hazard statements:

Non-applicable

### **Precautionary statements:**

Non-applicable

# Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

 $\label{lem:endocrine-disrupting properties: The product fails to meet the criteria. \\$ 

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

## 3.1 Substance:

Non-applicable

# 3.2 Mixture:

Chemical description: Aqueous mixture comoposed of colourants and acrylic resin

### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification		Concentration	
CAS:	2634-33-5	1,2-benzisothiazol-3(2H)-c	one <sup>(1)</sup>	Self-classified	
EC: Index: REACH:	220-120-9 613-088-00-6 01-2120761540-60-XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	♦	<0,05 %
CAS:	55965-84-9	reaction mass of 5-chloro-	2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) <sup>(1)</sup>	ATP ATP13	
	Non-applicable 613-167-00-5 Non-applicable	Regulation 1272/2008	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<b>♦♦</b>	<0,0015 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

Date of compilation: 06/08/2019 Revised: 05/01/2023 Version: 7 (Replaced 6) Page 1/10

<sup>\*\*</sup> Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



### Uni Paint W-XW-T

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

Identification		M-factor
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)		100
CAS: 55965-84-9 EC: Non-applicable		100

Identification	Specific concentration limit
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	% (w/w) >=0,05: Skin Sens. 1 - H317
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	% (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317

<sup>\*\*</sup> Changes with regards to the previous version

## **SECTION 4: FIRST AID MEASURES**

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

### By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

## By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## **SECTION 5: FIREFIGHTING MEASURES**

### 5.1 Extinguishing media:

# Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

# Unsuitable extinguishing media:

Non-applicable

## 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



### Uni Paint W-XW-T

### SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA).

Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

## For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

## 6.4 Reference to other sections:

See sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



### Uni Paint W-XW-T

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

## **DNEL (Workers):**

		Short ex	posure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,966 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6,81 mg/m³	Non-applicable

## DNEL (General population):

		Short ex	posure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1,2 mg/m³	Non-applicable

### PNEC:

Identification				
1,2-benzisothiazol-3(2H)-one	STP	1,03 mg/L	Fresh water	0,00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0,000403 mg/L
EC: 220-120-9	Intermittent	0,0011 mg/L	Sediment (Fresh water)	0,0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00499 mg/kg

### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

# E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# Uni Paint W-XW-T

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

## F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0 % weight V.O.C. density at 20  $^{\circ}$ C: 0 kg/m³ (0 g/L) Average carbon number: Non-applicable Average molecular weight: Non-applicable

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 10,73 kg/m³ (10,73 g/L)

EU limit for the product (Cat. A.A): 30 g/L (2010)

Components: 0000 - 10 % v/v

SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIES			
9.1	Information on basic physical and chemical proper	Information on basic physical and chemical properties:		
	For complete information see the product datasheet.			
	Appearance:			
	Physical state at 20 ºC:	Liquid		
	Appearance:	Not available		
	Colour:	White		
	Odour:	Not available		
	Odour threshold:	Non-applicable *		
	Volatility:			
	Boiling point at atmospheric pressure:	102 ºC		
	Vapour pressure at 20 ºC:	2333 Pa		
	Vapour pressure at 50 °C:	12293,92 Pa (12,29 kPa)		
	Evaporation rate at 20 ºC:	Non-applicable *		
	Product description:			
	Density at 20 ºC:	1490 kg/m³		
	Relative density at 20 °C:	Non-applicable *		
	Dynamic viscosity at 20 °C:	Non-applicable *		
	Kinematic viscosity at 20 °C:	Non-applicable *		
	Kinematic viscosity at 40 °C:	Non-applicable *		
	Concentration:	Non-applicable *		
	*Not relevant due to the nature of the product, not providing in	formation property of its hazards.		

Date of compilation: 06/08/2019 Revised: 05/01/2023 Version: 7 (Replaced 6) Page 5/10

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



### Uni Paint W-XW-T

Non-applicable \*

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

pH: Non-applicable \*
Vapour density at 20 °C: Non-applicable \*
Partition coefficient n-octanol/water 20 °C: Non-applicable \*
Solubility in water at 20 °C: Non-applicable \*
Solubility properties: Non-applicable \*
Decomposition temperature: Non-applicable \*

Flammability:

Melting point/freezing point:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Non-applicable \*

Autoignition temperature: 370 °C

Lower flammability limit: Non-applicable \*
Upper flammability limit: Non-applicable \*

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable \*
Oxidising properties: Non-applicable \*
Corrosive to metals: Non-applicable \*
Heat of combustion: Non-applicable \*
Aerosols-total percentage (by mass) of flammable Non-applicable \*

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

## **SECTION 10: STABILITY AND REACTIVITY**

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

# 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

# 10.3 Possibility of hazardous reactions:

 $Under the specified conditions, hazardous \ reactions \ that \ lead \ to \ excessive \ temperatures \ or \ pressure \ are \ not \ expected.$ 

## 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

## 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

- CONTINUED ON NEXT PAGE -

Date of compilation: 06/08/2019 Revised: 05/01/2023 Version: 7 (Replaced 6) Page 6/10

<sup>\*\*</sup> Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



### Uni Paint W-XW-T

### SECTION 11: TOXICOLOGICAL INFORMATION \*\*

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

#### B- Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
  - IARC: Talc (3); Distillates (petroleum), hydrotreated heavy paraffinic , < 3 % IP 346, > 20,5 cSt @  $40^{\circ}$ C (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

# E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	Non-applicable	
EC: 220-120-9	LC50 inhalation	Non-applicable	

<sup>\*\*</sup> Changes with regards to the previous version

Date of compilation: 06/08/2019 Revised: 05/01/2023 Version: 7 (Replaced 6) Page 7/10

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# Uni Paint W-XW-T

# SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

Identification	Acute toxicity		Genus
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87,12 mg/kg	Rabbit
EC: Non-applicable	LC50 inhalation	0,33 mg/L (4 h)	Rat

### 11.2 Information on other hazards:

## **Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

# SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

## 12.1 Toxicity:

## Acute toxicity:

Identification		Concentration	Species	Genus
1,2-benzisothiazol-3(2H)-one	LC50	2,2 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 2634-33-5	EC50	3 mg/L (48 h)	Daphnia magna	Crustacean
EC: 220-120-9	EC50	0,067 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: Non-applicable	EC50	>0.1 - 1 mg/L (72 h)		Algae

# 12.2 Persistence and degradability:

## Substance-specific information:

Identification	Degradability		Biodegradability	
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %

## 12.3 Bioaccumulative potential:

## Substance-specific information:

Identification	Bioaccumulation potential		
1,2-benzisothiazol-3(2H)-one	BCF	2	
CAS: 2634-33-5	Pow Log	1.45	
EC: 220-120-9	Potential	Low	

# 12.4 Mobility in soil:

Not available

### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

## 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

# 12.7 Other adverse effects:

Not described

# **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods:

<sup>\*\*</sup> Changes with regards to the previous version

<sup>\*\*</sup> Changes with regards to the previous version

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



### Uni Paint W-XW-T

### SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 12	waste paint and varnish other than those mentioned in 08 01 11	Non dangerous

### Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

## Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

#### **SECTION 14: TRANSPORT INFORMATION**

This product is not regulated for transport (ADR/RID,IMDG,IATA)

### **SECTION 15: REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Pyrithione zinc, 1,2-benzisothiazol-3(2H)-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13); reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

### Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Non-applicable

# Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The provider has carried out a chemical safety assessment

# **SECTION 16: OTHER INFORMATION**

# Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



### Uni Paint W-XW-T

### SECTION 16: OTHER INFORMATION (continued)

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- · New declared substances
  - 1,2-benzisothiazol-3(2H)-one (2634-33-5)
- · Removed substances
  - 1,2-benzisothiazol-3(2H)-one (2634-33-5)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- · Substances contained in EUH208:
- · New declared substances
- 1,2-benzisothiazol-3(2H)-one (2634-33-5)
- · Removed substances
- 1,2-benzisothiazol-3(2H)-one (2634-33-5)

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1A: H317 - May cause an allergic skin reaction.

### Classification procedure:

Non-applicable

### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

# Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

# Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET 
Date of compilation: 06/08/2019 Revised: 05/01/2023 Version: 7 (Replaced 6) Page 10/10