

**Unique identification code of the product:** MARMOLINE KL 101

It refers to all batches of MARMOLINE KL 101, produced after the issue of the present declaration

**Intended use /es:** Thin layer masonry mortar (T)

**Manufacturer /Distributor:**

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel +302295022225

Manufacturing plant: 1<sup>st</sup> km Provincial Road Malakasas - Markopoulou, 19011 Malakasa, Attica, Greece

**Systems of AVCP:** System 2+

**Harmonized standards:** EN 998-2:2016

**Notified body/ies:** TÜV HELLAS (TÜV NORD) (0654)

**Declared performance /s:**

Essential characteristics	Performance	Harmonised technical spec.
Compressive strength	M10	EN 998-2:2016 § 5.4.1 EN 1015-11
Shear strength	0.30 N/mm <sup>2</sup>	EN 998-2:2016 § 5.4.2.1.b Annex.C (tabulated)
Reaction to fire	Class A1	EN 998-2:2016 § 5.4.8 (without testing – organic content < 1.0%)
Water absorption	≤ 0.5 kg/m <sup>2</sup> min <sup>0.5</sup>	EN 998-2:2016 § 5.4.3 EN 1015-18
Water vapour permeability (μ)	5/20	EN 998-2:2016 § 5.4.4 EN 1745:2012, table A12 (tabulated)
Thermal conductivity	0.41 W/mK (λ <sub>10,dry</sub> P=50%)	EN 998-2:2016 § 5.4.6 EN 1745:2012, table A12 (tabulated)
Chloride content	≤ 0.1%	EN 998-2:2016 § 5.5.2 EN 1015-17
Workable life	240 min	EN 998-2:2016 § 5.2.1 EN 1015-9
Maximum grain size	1 mm	EN 998-2:2016 § 5.5.2
Correction time	10 min	EN 998-2:2016 § 5.5.3 EN 1015-9
Durability	NPD	EN 998-2:2016 § 5.4.7
Dangerous substances	See product's SDS	EN 998-2:2016 § 5.4.9

**The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:**

Malakasa, 15/4/2025

NORDIA S.A.  
QUARRYING AND INDUSTRIAL  
AND COMMERCIAL CO.S.A.  
VAT: EL 999211319  
364 KIFISSIAS AVENUE  
HALANDRI, 15233 - ATHENS GR  
TEL. 0030 - 210 - 68 96 480  
FAX. 0030 - 210 - 68 53 410

Dimitrios Poulakidas  
R&D-QC manager /Mortars