


CHRYSO® Dem Ekla 20 - DEV

Delayed mould release agent Vegetable emulsion



CHRYSO® Dem Ekla 20 - DEV is a delayed mould-release agent ready-to-use, formulated as an emulsion from vegetable-based components.

CHRYSO® Dem Ekla 20 - DEV is risk-free both for the user and the environment.

CHRYSO® Dem Ekla 20 - DEV is particularly recommended for use on concrete which require perfect surface aspect finishing

CHRYSO® Dem Ekla 20 - DEV can be used for non heat-cured concrete or up to 50°C curing temperature.

Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

Method of use

This product must be applied by spraying (all types of equipment), in a regular film, without any gaps or overload. Any excess would render mould-releasing difficult.

Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on www.chryso.com

Indicative characteristics

- Nature: liquid
- Colour: White
- Specific gravity: < 1,000
- Flash point: >100 °C
- Biodegradability: > 60% at 28 days as per NF EN ISO 9408 – OCDE 301 B
- Shelf life: 6 months

Domains of application

- Steam-cured or non steam-cured concrete
- Timber formworks
- Metallic formworks
- Plastic formworks
- Precast

Precautions

For special support or applications with white cement, it is advisable to run a compatibility test before any particular use.

Store in a dry place, away from light and any source of heat.



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on www.chryso.com.

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 41 17 18 19 - Fax: +33 (0)1 41 17 18 80

