DECLARATION OF PERFORMANCE



under regulation (EU) No 305/2011 and the amendment of Annex III, (EU) No 574/2014 No: 265 MAR-CPR



Unique identification code of the product: MARMOLINE LM 400

It refers to all batches of MARMOLINE LM 400, produced after the issue of the present declaration

Intended use /es: General purpose masonry mortar (G)

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel +302295022225 Manufacturing plant: 1st km Malakasas – Markopoulou Road, 19011 Malakasa, Attica, Greece

Systems of AVCP: System 2+

Harmonized standards: EN 998-2:2016

Notified body/ies: TÜV HELLAS (TÜV NORD) (0654)

Declared performance /s:

Essential characteristics	Performance	Harmonised technical spec.
Compressive strength	M10	EN 998-2:2016 § 5.4.1
		EN 1015-11
Shear strength	0.15 N/mm²	EN 998-2:2016 § 5.4.2.1.b
		Annex.C (tabulated)
Reaction to fire	Class A1	EN 998-2:2016 § 5.4.8
	C1055 711	(without testing – organic content< 1,0%)
Water absorption	\leq 0.5 kg/m ² min ^{0.5}	EN 998-2:2016 § 5.4.3
		EN 1015-18
Water vapour permeability (μ)	15/35	EN 998-2:2016 § 5.4.4
		EN 1745:2012, table A12 (tabulated)
Thermal conductivity	0.60 W/mK	EN 998-2:2016 § 5.4.6
	$(\lambda_{10,dry} P=50\%)$	EN 1745:2012, table A12 (tabulated)
Chloride content	≤ 0.1%	EN 998-2:2016 § 5.5.2
		EN 1015-17
Workable life	130 min	EN 998-2:2016 § 5.2.1
		EN 1015-9
Durability	NPD	EN 998-2:2016 § 5.4.7
Dangerous substances	See product's SDS	EN 998-2:2016 § 5.4.9

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Malakasa, 5/9/2024

QUARRYING AND INDUSTRIAL AND COMMERCIAL CO.S.A. VAT: ED 999211819 364 KIRISSIAS AVENUE HALANDRI 16238 ATHENS OF TEL. 0030 210 68 63 410

Vivi Dilaveri

Director of Marmoline Business Unit, Nordia S.A.