

www.marmoline.gr e-mail: info@nordia.gr

Tel.: (+30) 22950 22225 Fax: (+30) 22950 22120

MS 33

Transparent silicone based water repellent without solvents

DESCRIPTION

Highly-penetrating transparent silicone based sealant for absorbent surfaces. Ready to use, solvent-free, user and environmentally friendly.

FIELDS OF APPLICATION

Use it for the waterproofing and protection of common and coloured cementitious plasters, as well as on any other absorbent surface such as concrete, tiles, cementitious mortars, mosaic floors of terraces, absorbent rocks, natural stones, etc. It protects floors and unpolished marbles from water and dirt. It protects natural colours of renders and natural stones without being flaking and shining. It stabilizes the shade of coloured cementitious coatings. It waterproofs and protects tile joints.

CHARACTERISTICS/ADVANTAGES

- Transparent Odourless
- It does not contain organic solvents.
- Anti-alkaline.
- Waterproofing.
- It does not create a film.
- It does not flake.
- It maintains the breathability of the coating from inside
- It stabilizes the shade of coloured renders.
- It reduces pollutants retention.

PRODUCT INFORMATION

NORDIA S.A.

Packaging	Plastic containers of 5 kg and 20 kg.
	Palette of 300 kg, 60 containers of 5 kg.
	Palette of 480 kg, 24 containers of 20 kg
Storage conditions	In the original, closed, sealed and indestructible package, protected from direct sunlight and frost and at temperatures from +5°C to + 30°C.
Lifetime	12 months from production date

TUVNORD
TÜV HELLAS S.A.

ISO 9001

tvvhellas gr



MS33 Version: 09/25 Page 1 of 2



www.marmoline.gr

e-mail: info@nordia.gr Tel.: (+30) 22950 22225

Fax: (+30) 22950 22120

APPLICATION INFORMATION

Environmental temperature

from + 5 °C to + 35 °C

Consumption

0.2 - 1.0 kg/m², depending on the surface.

APPLICATION INSTRUCTIONS

Stir before use.

Make sure to repair any cracks on the surface, before application.

Apply with a paint roller, indissoluble or dissolved in water up to 30%, in two or more coats, until the surface is fully covered.

The required quantity depends on the absorbency of the surface and the desired result.

Do not use it on organic renders (like MARMOLINE SVR

HEALTH, SAFETY & ENVIROMENTAL PROTECTION

VOC: Maximum V.O.C. content: 29 g/L (20 °C). EU limit for the product (Category. A. h. WB): 30 g/L (2010). Detailed information instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website www.marmoline.gr or upon request.

LEGAL NOTICES

We guarantee the quality of the product, in terms of its technical specifications, as presented in the technical data sheet. This guarantee is strictly only for the available product and in no case the final result from its application, which depends to a large extent on the experience and quality of work of each user, as well as the conditions of application. It is recommended that the user apply the product on a small scale and after making sure of the result, then use it in his project. Publication of this technical data sheet supersedes any previous version. MARMOLINE reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



