

per Paint

DÉCOR – SUPER PAINT ELASTOMERIC PROTECTIVE WALL PAINT

3 in 1. Paints, insulates and protects

Description: Acrylic, elastomeric, high strength

protective/waterproofing paint for exterior walls.

Usages: It combines the properties of a paint and a water-

repellent liquid in one product, by creating an

elastic protective membrane.

It is applied on all types of surfaces, such as plaster, concrete, cement board, external thermal

insulation composite systems.

The flexible film covers and hides capillary cracks, making uniform pinhole-free jobs easier and faster to achieve. It incorporates a MARMOLINE

Dirt Pick-Up Resistance (DPR) technology combined with a high solid volume content

that provides a longest lasting waterproofing membrane.

Product Coverage: 10 m² /lt

information: Density: 1.46 + 0.02 kg/lt

Colours: According to colour palette in more than a thousand of shades

Advantages: • Exceptional hydrophobia (lotus effect).

• Ensures waterproofing - watertightness of the brickwork

Fiber reinforced

Seals and bridges capillaries and microcracks

• Self-cleaning. Barrier against atmospheric pollutants

Excellent resistance to UV rays

• Washable with a soft sponge.

Packing: Available in 750 ml, 5 lt &10 lt plastic containers

Storage: Keep this product in a shadowed place and avoid exposure to very high

temperature or frost (optimum storing temperature: +5°C to +35°C). Maximum

Page 1 of 2

NORDIA S.A.

Issue: 26/6/2021

HEAD OFFICE: 364 KIFISSIAS AV., 15233 CHALANDRI /ATHENS / GREECE, FACTORY: TEL: +302295022225, FAX: +302295022120 www.marmoline.gr - info@nordia.gr



ADVANCED BUILDING MATERIALS



storage time, in intact packaging: 12 months after production date.

Safety: May produce an allergic reaction. Safety data sheet available on request.

VOC: Maximum V.O.C. content: 13 g/L (20 °C). EU limit for the product (Cat. A. c.

WB): 40 g/L (2010)

Application mode:

• Stir before use.

- New surfaces must first be primed with the water-based primer MARMOLINE MST 11, undiluted or diluted up to 30% with water, depending on the surface.
- For fine cracks, and cracks arger than 0.5 mm, first fill the crack properly.
- Apply the next layer after 6-8 hours.
- Application temperature: +5°C to 35°C.

Instructions for health, safety and environmental protection: Keep out of reach of children - Avoid contact with skin and eyes — In case of contact with skin, wash with soap and water (do not use solvents) - In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice - Do not empty into drains or water sources - Manage the empty container responsibly and according to current legislation - Do not use empty container for storing food.

We guarantee the quality of all our products, on the basis of their technical specifications. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depend on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version

Page 2 of 2

NORDIA S.A.

TUV NORD
TOTALES

SOLUTION
TOTALES

TOT