

## VELVET LIQUID

### PROTECTIVE VARNISH FOR DECORATIVE CEMENT-BASED FINISHING SCREEDS

*It brings out the natural colours of decorative cement-based finishing screeds and stones*

**Description :** Acrylic-based, transparent (matt) polish for impregnation and protection from oils and dirt. Suitable for applications of MARMOLINE VELVET DECO decorative cement-based finishing screed. It is extremely resistant to UV rays. Non-shining, not turning yellow, no flaking

**Usages :** Use indoors and outdoors for waterproofing and protection of surfaces of decorative cement-based finishing screed, to prevent stains from domestic dirt and ensure easy cleaning with mild domestic cleaning products. Also use on surfaces of all kinds of natural stones.



**Advantages:** Ready to use - Water repellent - Oil repellent - Not turning yellow - No flaking - Durable - Interior and exterior use - Easy to apply with a paint roller or paintbrush.

**Packaging /distribution :** Plastic containers of 1 lt and 5 lt.

**Storage:** Containers must be stored in dry areas at a temperature from +5°C to +35°C and protected from sunlight and are preserved for at least 24 months from the date of production.

**Fire behaviour :** Highly flammable

**Safety :** Clear acrylic based liquid with organic solvents. It is harmful when inhaled or comes into contact with the body (Please consult the product's Safety Data Sheet)  
VOC - "Binding primers": Maximum VOC content in ready to use product < 750 gr/lit

**TECHNICAL FEATURES:**

<b>Form :</b>	Transparent liquid
<b>Odour :</b>	Acidic

**APPLICATION:**

**Consumption:** Use 1 lt per 5 to 8 m<sup>2</sup> depending on the substrate and its absorbency

**Application mode:**

- The surface of VELVET DECO decorative cement-based finishing screed must be thoroughly dry and clean. Check with a suitable moisture meter, that surface's moisture is less than 5%, or else problems may occur in application. Particular attention should be given to possible presence of moisture in the substrate, if VELVET DECO is applied outdoors.
- If there's dust on the surface, dry clean it with a broom or a vacuum, to remove any dirt. You can also clean the decorative cement surfaces (or stones) using a squeezed damp sponge, but do not leave any moisture on it
- If the application of the varnish is made on old stained surfaces, these should be thoroughly cleaned before application, using MARMOLINE cleaning products
- On new stone surfaces, the varnish should be applied at least 4 weeks after the adhesion and joint-filling of the stones.
- Before applying VELVET LIQUID varnish, you can apply the water based transparent silicone sealant MARMOLINE MS 33
- Stir VELVET LIQUID and apply it with a paint roller or paintbrush in 2 coats. The second coat should be applied 2 - 3 hours after the first one.
- Pay attention to ambient temperature during summer months. Avoid the very warm days and prefer morning hours for application
- After having applied the varnish, protect the surfaces from water for at least 24 hours.
- Clean the tools right after application, using a solvent.

*We guarantee the quality of our product on the basis of its technical specifications, but not the final result, which largely depends on the experience of each user and the application conditions. The user is advised to test the product on a small scale, and if he is satisfied by the result, to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version*