

DÉCOR – FLYING COLOURS EXTERIOR ACRYLIC PAINT FOR EXTERIOR USE

The house breathes colour

Description: Acrylic paint for exterior use. It spreads easily,

producing a matt, water resistant and vapour

permeable surface.

Suitable for any surface made of plaster, **Usages:**

concrete, gypsum board. Also for old, previously

painted surfaces

Product Coverage: $12 - 13 \text{ m}^2 / \text{lt}$

5 – 10% with water information: Dilution:

1.46 + 0.02 kg/ltDensity:

Application mode: Roller, brush or spray gun. It can also be applied with a brush,

sponge or a cloth, to create specific texture.

Drying: In touch: 50 – 60 minutes, depending on the weather conditions.

2nd layer: After 3 - 3.5 hours

Colours: According to colour palette in more than a thousand of shades

• Easy to work with Advantages:

Excellent coverage

Strong adhesion

Resistant to bad weather conditions

Long lasting

• Prevents mould

Allows vapour permeability of the surface

Washable with a soft sponge.

Available in 750 ml, 3 lt &10 lt plastic containers Packing:

Storage: Keep this product in a shadowed place and avoid exposure to very high

temperature or frost (optimum storing temperature: +5°C to +35°C). Maximum

storage time, in intact packaging: 12 months after production date.



Issue: 2/8/2019 Page 1 of 2 HEAD OFFICE: 364 KIFISSIAS AV., 15233 CHALANDRI /ATHENS / GREECE, TEL: +302106896480, FACTORY: TEL: +302295022225, FAX: +302295022120 www.marmoline.gr - info@marmoline.gr



ADVANCED BUILDING MATERIALS



VOC class:

"Paints – Exterior walls of mineral substrate -WB". VOC limit: 40 gr/lt. Max VOC of product ready to use: 39 gr/lt.

Application mode:

- Make sure that the surfaces are clean and free of grease.
- Remove loose parts or peelings of previous paint.
- New surfaces or surfaces that were in a poor condition and were repaired /covered with stucco, should be first primed with the MARMOLINE MST 11 primer, either undiluted or diluted by up to 30% with water
- Stir FLYING COLOURS well before use.
- You may dilute it by adding 5-10% water.
- Apply in 2 layers

Instructions for health, safety and environmental protection: Keep out of reach of children - Avoid contact with skin and eyes — In case of contact with skin, wash with soap and water (do not use solvents) - In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice - Do not empty into drains or water sources - Manage the empty container responsibly and according to current legislation - Do not use empty container for storing food.

We guarantee the quality of all our products, on the basis of their technical specifications. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depend on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version



