

Unique identification code of the product: MARMOLINE AQUATA 240

Cementitious brushable waterproofing mortar

It refers to all batches of MARMOLINE AQUATA 240, produced after the issue of the present declaration

Intended use /es: Protection of concrete surfaces - Coating - moisture control**Manufacturer /Distributor:**

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225

Manufacturing plant: 1st km Provincial Road Malakasas - Markopoulou, 19011 Malakasa, Attica, Greece**Systems of AVCP:** System 2+, System 4 (reaction to fire)**Harmonized standards:** EN 1504-2:2004 - Principles 2.2 (C), 8.2 (C)**Notified body/ies:** TUV AUSTRIA HELLAS (0906)**Declared performance /s:**

| Essential characteristics | Performance | Harmonised technical spec. |
|----------------------------|--|--|
| Water vapour permeability: | $S_D < 5 \text{ m (class I)}$ | EN 1504-2:2004, table 1 [2 – 2.2(c)], table ZA.1e & §5.2, table 5 (7) EN ISO 7783-2 |
| Capillary absorption: | $w \leq 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$ | EN 1504-2:2004, table 1 [2 – 2.2(c)], table ZA.1e & §5.2, table 5 (8) EN 1062-3 |
| Adhesion strength: | $\geq 1.0 \text{ N/mm}^2$ | EN 1504-2:2004, table 1 [2 – 2.2(c)], table ZA.1e & §5.2, table 5 (15) EN 1542 |
| Reaction to fire: | F | EN 1504-2:2004, table ZA.1d & §5.2, table 5 (16) & §5.4 |
| Dangerous substances: | Complies with §5.3 | EN 1504-2:2004, table ZA.1d & §5.3 |

The performance of the product identified above is in conformity with the set of declared performance/s.**This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above.****Signed for and on behalf of the manufacturer by:**

Malakasa, 21/1/2025

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211319
364 KIFISSIAS AVENUE
CHALANDRI, 15233 - ATHENS GR
TEL. 0030 - 210 - 68 96 480
FAX. 0030 - 210 - 68 53 410

Dimitrios Poulakidas
R&D-QC manager /Mortars