

## DÉCOR – FLYING COLOURS INTERIOR

### EMULSION PAINT FOR INTERIOR USE

*Your dreams become colourful*

**Description :** Emulsion paint for interior use. It has excellent levelling properties, producing a uniform matt velvet surface.

**Usages :** Suitable for new surfaces, levelled or not with putty, made of plaster, concrete, gypsum board, cement board. Also for old, previously painted surfaces.



**Product information:**

Coverage:	13 – 14 m <sup>2</sup> /lt
Dilution:	5 – 10% with water
Density:	1.48 ± 0.02 kg/ lt
Application mode:	Roller, brush or spray gun
Drying:	In touch: 50 – 60 minutes, depending on the weather conditions.
2 <sup>nd</sup> layer:	After 3 – 3.5 hours
Colours:	According to colour palette in more than a thousand of shades

**Advantages:**

- Easy to work with
- Odourless
- Excellent coverage
- Resistance to frequent washing and detergents
- Resistance to yellowing caused by smoking
- Allows vapour permeability of the surface
- Washable with a soft sponge.

**Packing:** Available in 750 ml, 3 lt & 10 lt plastic containers

**Storage:** Keep this product in a shadowed place and avoid exposure to very high temperature or frost (optimum storing temperature: +5°C to +35°C). Maximum storage time, in intact packaging: 12 months after production date.

- Safety:** May produce an allergic reaction. Safety data sheet available on request.  
VOC: Maximum V.O.C. content: 11 g/L (20 °C). EU limit for the product (Cat. A. a. WB): 30 g/L (2010)
- Application mode:**
- Make sure that the surfaces are clean and free of grease.
  - Remove loose parts or peelings of previous paint.
  - For puttying and leveling of surfaces, use the acrylic stucco MARMOLINE STUCCO BIANCO, which can be applied with a spatula, or the ready-to-use acrylic stucco MARMOLINE STUCCO PASTE, in the form of paste.
  - New surfaces or surfaces that were in a poor condition and were repaired /covered with stucco, should be first primed with the MARMOLINE MST 11 primer, either undiluted or diluted by up to 30% with water
  - Stir FLYING COLOURS well before use.
  - You may dilute it by adding 5-10% water.
  - Apply in 2 layers
- Instructions for health, safety and environmental protection :** Keep out of reach of children - Avoid contact with skin and eyes – In case of contact with skin, wash with soap and water (do not use solvents) - In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice - Do not empty into drains or water sources - Manage the empty container responsibly and according to current legislation - Do not use empty container for storing food.

*We guarantee the quality of all our products, on the basis of their technical specifications. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depend on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version*