

METALWOOD

High quality alkyd-based paint

DESCRIPTION

High quality enamel paint with anti-corrosive properties.

APPLICATION FIELDS

Suitable for metal and wooden surfaces, such as railings, doors, windows, vehicle bodies, furniture etc.

It has excellent resistance to wash and yellowing, providing a perfect finish.

CHARACTERISTICS/ ADVANTAGES

- Strong adhesion and hardness
- Resistant to impact and wear
- Retains its shine and hue

PRODUCT INFORMATION

Packaging: 750 ml & 2.5 lt metal cans

Storage: Protect from freezing. Store at room temperatures, from 5°C to 35°C. Seal the container for future use

TECHNICAL CHARACTERISTICS

Density: 1.00 - 1.40 gr/ml (ISO 2811)

Viscosity: 180 – 220 s (Ford Cup No 4)

Gloss degree at 60°: 85 – 90%

Colours: Available in white, dark green and black as well as in an unlimited number of color shades, through DÉCOR TINTING SYSTEM

APPLICATION INFORMATION

Performance: 13 – 15 m² /lt

Dilution:

Application with brush or roller: dilute up to 10% with white spirit or brush thinner.

Application with spray gun: dilute up to 15% with nitro or spray gun thinner.

Application mode: Roller, brush or spray gun.

Drying: 4 – 8 hours.

Recoating: After 24 hours

HEALTH, SAFETY & ENVIROMENTAL PROTECTION

Subject to directive 2004/42/E.C.: VOC class: "One-pack performance coatings (SB) (A/i)". Limit value for this product: 500 g/l (2010). This product ready for use contains max V.O.C. 499g/l.

Detailed information and instructions regarding the safe management of the product and in matters of Health & Safety, are provided in the most recent Safety Data Sheet (SDS), copies of which are available on the company's website <https://marmoline.gr/> or upon request

APPLICATION INSTRUCTIONS

- Prepare the application surface, so that it is clean and dry, free of dust, grease or oils, disintegrated parts etc.
- Ensure good ventilation of the application area and wear appropriate protective means.
- For better anti-corrosive protection under hard weather conditions, it is suggested prior priming of the surfaces with MARMOLINE Rust Off
- For application on wooden surfaces, these should first be prepared with a suitable white undercoat (velatura)
- MARMOLINE MetalWood should be used in well ventilated area
- It is not suggested to use the products in temperatures below 5°C and above 40°C
- Remove from the tools the product that is left over, before cleaning them with solvent

LEGAL NOTICE

We guarantee the quality of all our products, based on their technical specifications, as described in the Declaration of Performance (CE) and this Technical Data Sheet. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depends on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. All data stated in this Technical Data Sheet are based on laboratory tests. The really measurable data might differentiate due to conditions that are not subject to our control. The recommendations and implementation instructions must be considered by the user as indicative, and always with given that the product has been traded and traded and stored according to its instructions. As it is not possible to control the parameters/conditions of its application product in practice, no guarantee is provided for the final result of each application. Consequently, no legal liability of the Company can be established based on the information and instruction given in this Technical Data Sheet. The Company reserves the right to modify data listed in this Product Data Sheet, with no previous warning. Users must refer to the latest version of the product Technical Data Sheet.