

DECLARATION OF PERFORMANCE

under regulation (EU) No 305/2011
and the amendment of Annex III, (EU) No 574/2014
No: 007 MARMO-CPR

**Unique identification code of the product:** MARMOLINE FLEX 3000

Type: Improved highly deformable cementitious adhesive for tiles (C2S2) with reduced slip (T) and extended open time (E).

It refers to all batches of MARMOLINE FLEX 3000, produced after the issue of the present declaration

Intended use /es: Adhesive for tiles

Manufacturer /Distributor:

NORDIA S.A., Head Office: 364 Kifissias av., 15233 Chalandri /Greece, tel: +302295022225

Manufacturing plant: 1st km Malakasas – Markopoulou Road, 19011 Malakasa, Attica, Greece

Systems of AVCP: System 3, System 4 (reaction to fire)

Harmonized standards: EN 12004:2007 + A1:2012

Notified body/ies:

Declared performance /s:

Essential characteristics	Performance	Harmonized technical spec.
Initial tensile adhesion strength (after 28 days):	$\geq 1.0 \text{ N/mm}^2$	EN 12004:2007+A1 § 5.4 Table 5 EN 1348
Tensile adhesion strength after heat ageing :	$\geq 1.0 \text{ N/mm}^2$	
Tensile adhesion strength after water immersion :	$\geq 1.0 \text{ N/mm}^2$	
Tensile adhesion strength after freeze/thaw cycles:	$\geq 1.0 \text{ N/mm}^2$	
Reaction to fire:	E	EN 12004:2007+A1 § 4.4 EN 13501-1
Release of dangerous substances:	See product's SDS	EN 12004:2007+A1 § 4.5

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Malakasa, 21/1/2025

NORDIA S.A.
QUARRYING AND INDUSTRIAL
AND COMMERCIAL CO.S.A.
VAT: EL 999211319
364 KIFISSIAS AVENUE
HALANDRI - 15233 - ATHENS G
TEL. 0030 - 210 - 68 96 48
FAX. 0030 - 210 - 68 53 41

Dimitrios Poulakidas
R&D-QC manager /Mortars