

DÉCOR – UNI PAINT ACRYL

ACRYLIC CEMENT PAINT

Description : Acrylic cement paint suitable for exterior use. It is easily workable and has excellent leveling properties. It allows surface to “breath”.

Usages : Due to its special composition, it is highly resistant to alkalis, on new or re-painted surfaces and in adverse weather conditions. It offers great coverage and unrivaled performance.



Product information:

Coverage:	13 – 14 m ² /lt
Dilution:	5 – 10% with water
Density:	1.5 kg/ lt
Application mode:	Roller, brush or spray gun
Drying:	In touch: 50 – 60 minutes, depending on the weather conditions.
2 nd layer:	After 3 – 3.5 hours
Colours:	Available in two basic colors, white and gray, and in more than 1700 shades, using the coloring system of MARMOLINE

Advantages:

- Easy to work with
- Odourless
- Excellent coverage and resistance to adverse weather conditions
- Allows vapour permeability of the surface
- Washable with a soft sponge

Packing: Available in 750 ml, 3 lt & 9 lt plastic containers

Storage: Keep this product in a shadowed place and avoid exposure to very high temperature or frost (optimum storing temperature: +5°C to +35°C). Maximum storage time, in intact packaging: 12 months after production date.

Safety: May produce an allergic reaction. Safety data sheet available on request.
VOC: Maximum V.O.C. content: 8 g/L (20 °C). EU limit for the product (Cat. A. c. WB): 40 g/L (2010)

Application mode:

- Make sure that the surfaces are clean and free of grease.
- Remove loose parts or peeling of the old paint
- For puttying and leveling of the surfaces, use the acrylic stucco MARMOLINE STUCCO BIANCO or the acrylic putty, MARMOLINE STUCCO PASTE.
- On new surfaces or surfaces that were in poor condition and repaired, apply first the MARMOLINE MST 11 primer, undiluted or diluted up to 30% with water
- Stir UNI PAINT ACRYL well before use
- You may dilute the product with 5 – 10% water
- Apply in 2 layers

Instructions for health, safety and environmental protection :

Keep out of reach of children - Avoid contact with skin and eyes – In case of contact with skin, wash with soap and water (do not use solvents) - In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice - Do not empty into drains or water sources - Manage the empty container responsibly and according to current legislation - Do not use empty container for storing food.

We guarantee the quality of all our products, on the basis of their technical specifications. Such guarantee refers only to the products that we deliver for use and never to its application or final result, which largely depend on the experience and quality of work of each user and on the application conditions. The user is advised to test the product on a small scale, and if he is satisfied with the result, then to use the product on large scale in his project. This edition of technical data sheet automatically cancels any previous version